

# 2020 KLX<sup>®</sup>300R

**Kawasaki**  
Let the Good Times Roll<sup>®</sup>



 LIME GREEN



## POWER

<b>Engine</b>	4-stroke single, DOHC, liquid-cooled
<b>Displacement</b>	292cc
<b>Bore x Stroke</b>	78.0 x 61.2mm
<b>Compression Ratio</b>	11.0:1
<b>Fuel System</b>	DFI <sup>®</sup> with 34mm Keihin throttle body
<b>Ignition</b>	TCBI Electronic Advance
<b>Transmission</b>	6-speed, return shift with wet multi-disc manual clutch
<b>Final Drive</b>	Chain

<b>Rear Tire</b>	100/100-18
<b>Front Brakes</b>	Single 270mm petal disc with a dual-piston caliper
<b>Rear Brakes</b>	Single 240mm petal disc with single-piston caliper

## DETAILS

<b>Frame Type</b>	Tubular, Semi-Double Cradle
<b>Rake/Trail</b>	26.9° / 4.3 in
<b>Overall Length</b>	83.5 in
<b>Overall Width</b>	32.5 in
<b>Overall Height</b>	49.2 in
<b>Ground Clearance</b>	12.0 in / 11.8 CA model
<b>Seat Height</b>	36.4 in
<b>Curb Weight</b>	282.2 lb / 286.6 lb. CA model*
<b>Fuel Capacity</b>	2.1 gal
<b>Wheelbase</b>	56.5 in
<b>Color Choices</b>	Lime Green
<b>Warranty</b>	6 Months

## PERFORMANCE

<b>Front Suspension / Wheel Travel</b>	43mm inverted telescopic fork with adjustable compression damping / 11.2 in
<b>Rear Suspension / Wheel Travel</b>	Uni-Trak <sup>®</sup> gas charged shock with piggyback reservoir with adjustable compression, rebound damping and spring preload / 11.2 in
<b>Front Tire</b>	80/100-21

Scan with camera to view videos, key features and more.



\*Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied). KAWASAKI CARES: Read Owner's Manual and all on-product warnings. Always wear a helmet, eye protection and proper apparel. Never ride under the influence of drugs or alcohol. Adhere to the maintenance schedule in your Owner's Manual. ©2024 Kawasaki Motors Corp., U.S.A. Specifications subject to change. Visit [hawaii.kawasaki.com](http://hawaii.kawasaki.com) for full product details.