

# 2020 CONCOURS<sup>®</sup>14 ABS

**Kawasaki**  
Let the Good Times Roll<sup>®</sup>



METALLIC MATTE FUSION SILVER/METALLIC SPARK BLACK



## POWER

Engine	4-stroke, 4-cylinder, DOHC, 4-valve, liquid-cooled
Displacement	1,352cc
Bore x Stroke	84.0 x 61.0mm
Compression Ratio	10.7:1
Fuel System	DFI <sup>®</sup> with 40mm throttle bodies (4)
Ignition	TCBI with digital advance
Transmission	6-speed
Final Drive	Tetra-Lever shaft drive

Rear Tire	190/50 ZR-17
Front Brakes	Dual floating 310mm petal-style discs with four-piston calipers, ABS
Rear Brakes	Single 270mm petal-style disc, single-piston caliper, ABS

## PERFORMANCE

Front Suspension / Wheel Travel	43mm inverted, telescopic fork with adjustable rebound damping and spring preload/4.4 in
Rear Suspension / Wheel Travel	Tetra-Lever with stepless rebound damping adjustment and remote spring preload adjuster/5.4 in
Front Tire	120/70 ZR-17

## DETAILS

Frame Type	Monocoque Aluminum
Rake/Trail	26.0°/4.4 in
Overall Length	87.8 in
Overall Width	31.1/39.4 wo/w saddlebags
Overall Height	52.9 in/57.7 in (windshield down/up)
Ground Clearance	4.9 in
Seat Height	32.1 in
Curb Weight	690.2 lb (672.5 w/o saddlebags)*
Fuel Capacity	5.8 gal
Wheelbase	59.8 in
Color Choices	Metallic Matte Fusion Silver/Metallic Spark Black
Warranty	36 Month Limited Warranty

Scan with camera to view videos, key features and more.



\*Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied). KAWASAKI CARES: Read Owner's Manual and all on-product warnings. Always wear a helmet, eye protection and proper apparel. Never ride under the influence of drugs or alcohol. Adhere to the maintenance schedule in your Owner's Manual. ©2024 Kawasaki Motors Corp., U.S.A. Specifications subject to change. Visit [hawaii.kawasaki.com](http://hawaii.kawasaki.com) for full product details.