## 2020 MULE 4000 TRANS<sup>™</sup>



BRIGHT WHITE



| POWER   |  | Rear Brakes   | Drum  |
|---|--|---|---|
| Engine<br>Displacement<br>Maximum Torque<br>Bore x Stroke<br>Compression Ratio<br>Fuel System<br>Transmission | <ul> <li>4-stroke, 2-cylinder, OHV, 90° V, liquid-cooled, gas</li> <li>617cc</li> <li>34.7 lb-ft @ 2500 rpm</li> <li>2.99x2.68 in</li> <li>10:3:1</li> <li>DFI® with 34mm Mikuni throttle body</li> <li>Continuously Variable Transmission (CVT) with (H,N,R)</li> </ul> | Ground Clearance<br>Fuel Capacity<br>Turning Radius<br>Cargo Bed<br>Dimensions<br>(LxWxH)<br>Cargo Bed Load<br>Capacity<br>Payload Capacity | 7.7 in<br>6.3 gal<br>12.8 ft<br>50.4 x 47.6 x 11.2 in (2-person),30.3 x 47.6 x 11.2 in (4-<br>person)<br>800 lb (2-person),400 lb (4-person)<br>1330 lb |
| Final Drive<br>Engine Braking<br>Alternator Output  | 2WD, shaft. Dual mode rear differential with<br>differential lock<br>No<br>23 amp  | Seating Capacity<br>Towing Capacity<br>Lighting   | 2-4<br>1200 lb<br>(2) Halogen headlights, (2) Halogen tail/brake lights   |
| (max)   | 25 amp   | DETAILS   |   |

**Overall Length** 

128.5 in

## CAPABILITY

| Front Suspension /<br>Wheel Travel | MacPherson Strut/3.9 in       | Overall Width  | 58.5 in   |
|------------------------------------|-------------------------------|----------------|---|
| wheet fravet                       |                               | Overall Height | 78.1 in   |
| Rear Suspension /<br>Wheel Travel  | DeDion Axle/2.8 in            | Curb Weight    | 1514.1 lb*  |
| Front Tires                        | 23x11.00-10                   | Wheelbase      | 85.2 in   |
| Rear Tires                         | 23x11.00-10                   | Instruments    | Parking brake warning light, coolant temperature warning light, 12V DC outlet, fuel gauge, hour meter |
| Steering                           | Electric Power Steering (EPS) | Color Choices  | Bright White  |
| Park Brake Type                    | Independent, Mechanical Drum  | Warranty       | Kawasaki 3-Year Limited Warranty  |
| Front Brakes                       | Drum                          | mananty        |   |
|                                    |                               |                |   |





\*Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied). KAWASAKI CARES: Read Owner's Manual and all on-product warnings. Always wear protective gear appropriate for the use of this vehicle. Never operate under the influence of drugs or alcohol. Protect the environment. The Kawasaki MULE<sup>TM</sup> side x side is an off-highway vehicle only, and is not designed, equipped or manufactured for use on public streets, roads or highways. Obey the laws and regulations that control the use of your vehicle. ©2025 Kawasaki Motors Corp., U.S.A. Specifications subject to change. Visit hawaii.kawasaki.com for full product details.

