## **MULE PRO-FXT™**







## **POWER**

**Engine** 4-stroke, 3-cylinder, DOHC, liquid-cooled, gas

Displacement 812cc

**Maximum Torque** 48.0 lb-ft @ 3500 rpm

**Bore x Stroke** 2.83x2.62 in

**Compression Ratio** 9.5:1

**Fuel System** DFI® with 34mm throttle body

Transmission Continuously Variable Transmission (CVT) with (H,L,N,R)

**Final Drive** Selectable 2WD/4WD, shaft. Dual mode rear differential

with differential lock

**Engine Braking** 

**Alternator Output** 75 amp

(max)

**Ground Clearance** 10.2 in

**Fuel Capacity** 7.9 gal

**Turning Radius** 16.0 ft

**Cargo Bed Load** 

**DETAILS** 

**Overall Height** 

**Cargo Bed** 42.7 x 53.7 x 11.0 in (3-person)22.0 x 53.7 x 11.0 in (6-**Dimensions (LxWxH)** 

person)

models) Capacity

**Payload Capacity** 1616 lb (1264 lb California model)

**Seating Capacity** 3-person (1 row), 6 person (2 row)

**Towing Capacity** 2000 lb

Lighting (2) Halogen headlights, (2) Halogen tail/brake lights

## CAPABILITY

**Wheel Travel** 

Double wishbone/8.7 in Front Suspension / **Wheel Travel** 

Rear Suspension / Double wishbone/8.5 (L) /8.7 (R) in

**Front Tires** 26x9.00-12, radial **Rear Tires** 26x11.00-12, radial Rack-and-pinion Steering

**Park Brake Type** Independent, Mechanical Disc

**Front Brakes** Dual Disc, 2 piston caliper **Rear Brakes** Dual Disc, 1 piston caliper **Overall Length** 133.3 in

**Overall Width** 64.0 in

**Curb Weight** 1887.5 lb\*

Wheelbase 92.3 in

Instruments Multi-function display includes digital speedometer,

77.6 in

fuel gauge, odometer, hour meter, clock, dual trip meters, 2WD/4WD indicator, water temperature warning indicator, oil pressure warning indicator, fuel injection warning indicator, CVT warning indicator, neutral, reverse and parking indicators, seatbelt reminder lamps

1000 lb (3-person)350 lb (6-person)(600 lb for California

**Wheel Type** Steel

**Color Choices** Super Black

Warranty Kawasaki 3-Year Limited Warranty

Scan with camera to view videos, key features and more.

