## **MULE PRO-MX™ EPS**









## **POWER**

**Engine** 4-stroke, single cylinder, SOHC, 4-valve liquid-cooled

Displacement 695cc

**Maximum Torque** 42.7 lb-ft @ 5000 rpm

**Bore x Stroke** 4.02x3.35 in

**Compression Ratio** 10.3:1

**Fuel System** DFI® with 44mm throttle body

Transmission Continuously Variable Transmission (CVT) with

centrifugal clutch, (H,L,N,R)

**Final Drive** Selectable 2WD/4WD, shaft. Dual mode rear differential

with differential lock

**Engine Braking** 

CAPABILITY

**Alternator Output** 35.7 amp

(max)

**Ground Clearance** 10.6 in

**Fuel Capacity** 9.5 gal

**Turning Radius** 14.0 ft

**Cargo Bed** 

**Dimensions (LxWxH)** 

**Cargo Bed Load** 

Capacity

**Payload Capacity** 1200 lb

**Seating Capacity** 

**Towing Capacity** 1500 lb

Lighting (2) Halogen headlights, (2) LED headlights

33.4 x 44.1 x 9.1 in

700 lb (600 lb California models)

Front Suspension / Double wishbone/8.6 in **Wheel Travel** 

Rear Suspension / Double wishbone/9.1 in **Wheel Travel** 

**Front Tires** 25x10.00-12, radial **Rear Tires** 25x10.00-12, radial

Electric Power Steering (EPS), Tilt steering **Steering** 

**Park Brake Type** Independent, Mechanical Disc **Front Brakes** Dual Disc, 2 piston caliper

**Rear Brakes** Dual Disc, 1 piston caliper

## **DETAILS**

**Overall Length** 110.0 in **Overall Width** 60.0 in **Overall Height** 74.4 in

**Curb Weight** 1587.6 lb\*

Wheelbase 78.9 in

Instruments Multi-function display includes digital speedometer,

fuel gauge, odometer, hour meter, clock, dual trip meters, 2WD/4WD indicator, water temperature warning indicator, EPS warning indicators, neutral, reverse and parking indicators, differential indicator lamp, seatbelt

reminder lamps

**Wheel Type** 

**Color Choices** Timberline Green, Bright White

Warranty Kawasaki 3-Year Limited Warranty

Scan with camera to view videos, key features and more.

