## MULE SX™ 4x4 FI









## **POWER**

Engine 4-stroke, single-cylinder, OHV, air-cooled

Displacement 401cc

Maximum Torque 21.4 lb-ft @ 2400 rpm

Bore x Stroke 3.23x2.99 in

Compression Ratio 8.6:

Fuel System Fuel injection

**Transmission** Continuously Variable Transmission (CVT) with (H,L,N,R)

Final Drive Selectable 2WD/4WD, shaft. Dual mode rear differential

with differential lock

Engine Braking N

**Alternator Output** 

(max)

Ground Clearance 6.7 in
Fuel Capacity 4.2 gal

Turning Radius 10.8 ft

Cargo Bed Dimensions (LxWxH)

**Rear Brakes** 

35.6 x 40.9 x 9.6 in

Cargo Bed Load Capacity

400 lb

Drum

Payload Capacity

Seating Capacity
Towing Capacity

| -

915 lb

Towning Capacity

1100 lb\*

(2) Halogen headlights, (2) Halogen tail/brake lights

## **CAPABILITY**

Front Suspension / MacPherson Strut/3.1 in Wheel Travel

Rear Suspension / Wheel Travel Unit Swingarm/3.1 in

Front Tires

24x9.00-10

22.9 amp

**Rear Tires** 24x11.00-10

Steering

Rack-and-pinion, Tilt steering

Park Brake Type

Independent, Mechanical Drum

Front Brakes Drum

## **DETAILS**

**Curb Weight** 

Warranty

Lighting

Overall Length 106.7 in

Overall Width 52.6 in

Overall Height 70.9 in

verall neight 70.9 iii

Wheelbase 70.1 in

**Instruments** Fuel gauge, hour meter, oil temp light, parking brake

light

1031.9 lb\*\*

**Color Choices** Timberline Green, Dark Royal Red

Kawasaki 3-Year Limited Warranty

Scan with camera to view videos, key features and more.

