
NINJA® ZX™-10R ABS









POWER

Engine 4-stroke, 4 cylinder, DOHC, 4-valve, Liquid-cooled

Displacement 998cc

Bore x Stroke 76.0 x 55.0mm

Compression

Ratio

13.0:1

Fuel System DFI® w/47mm Mikuni throttle bodies (4) with oval

sub-throttles, two injectors per cylinder

Ignition TCBI with digital advance and Sport-Kawasaki

Traction Control (S-KTRC)

Transmission 6-speed, return shift

Final Drive Sealed chain

Electronic Rider

Aids

Kawasaki Launch Control Mode (KLCM), Kawasaki Intelligent anti-lock Brake System (KIBS), Kawasaki Sport Traction Control (S-KTRC), Kawasaki Engine Braking Control, Kawasaki Quick Shifter (KQS) (upshift & downshift), Kawasaki Cornering Management Function (KCMF), Power

Modes, Electronic Steering Damper

PERFORMANCE

Front Suspension / Wheel Travel

43mm inverted Balance Free Fork, adjustable stepless rebound and compression damping, spring preload adjustability/4.7 in

Rear Suspension / Wheel Travel

Horizontal back-link with Balance Free gascharged shock, stepless, dual-range (low-/highspeed) compression damping, stepless rebound damping, fully adjustable spring preload/4.5 in Front Tire 120/70 ZR17

Rear Tire 190/55 ZR17

Front Brakes Intelligent Braking (KIBS), Brembo dual semi-

floating 330mm discs with dual radial mounted

monobloc 4-piston calipers

Rear Brakes KIBS-controlled, single 220mm disc with

aluminum single-piston caliper

DETAILS

Frame Type Aluminum perimeter

Rake/Trail 25.0°/4.2 in

Overall Length 82.1 in

Overall Width 29.1 in

Overall Height 45.1 in

Ground Clearance 5.7 in

Seat Height 32.9 in

Curb Weight 454.2 lb*

Fuel Capacity 4.5 gal

Wheelbase 56.7 in

Special Features N/A

Color Choices Metallic Spark Black/ Metallic Flat Spark Black

Warranty 12 Month Limited Warranty



