2020 VULCAN[®] 900 CUSTOM









Uni-Trak[®] swingarm, 7-way adjustable spring

POWER

Engine	4-stroke, 55° V-twin, 4 valves per cylinder, SOHC, liquid-cooled
Displacement	903cc/55.10 cu in
Bore x Stroke	88.0 x 74.2mm
Compression Ratio	9.5:1
Maximum Torque	58.2 lb-ft @ 3500 rpm
Fuel System	DFI® 34mm throttle bodies (2), with sub- throttle valves
Ignition	TCBI with digital advance
Transmission	5-speed with positive neutral finder
Final Drive	Kevlar-reinforced belt

PERFORMANCE

Front Suspension / Wheel Travel 41mm hydraulic telescopic fork/5.9 in

Wheel TravelFront Tire80/90x21Rear Tire180/70x15Front BrakesSingle 300mm hydraulic discRear BrakesSingle 270mm hydraulic disc

preload/4.1 in

DETAILS

Rear

Suspension /

Frame Type	Double cradle, high-tensile steel
Overall Length	94.7 in
Overall Width	35.2 in
Overall Height	44.1 in
Ground Clearance	5.5 in
Seat Height	27.0 in
Curb Weight	610.8 lb*
Fuel Capacity	5.3 gal
Wheelbase	64.8 in
Color Choices	Metallic Matte Graphite Gray/Metallic Flat Spark Black
Warranty	12 Month Limited Warranty





*Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied). KAWASAKI CARES: Read Owner's Manual and all on-product warnings. Always wear a helmet, eye protection and proper apparel. Never ride under the influence of drugs or alcohol. Adhere to the maintenance schedule in your Owner's Manual. ©2025 Kawasaki Motors Corp., U.S.A. Specifications subject to change. Visit hawaii.kawasaki.com for full product details.