²⁰²¹ **W800**







POWER

| Engine | 4-stroke, vertical twin, SOHC, 8 valves, air- cooled |
|----------------------|---|
| Displacement | 773cc |
| Bore x Stroke | 77.0 x 83.0mm |
| Compression Ratio | 8.4:1 |
| Maximum Torque | 46.4 lbft. |
| Fuel System | DFI®with 34mm throttle bodies (2) |
| Ignition | TCBI w/digital advance |
| Transmission | 5-speed, return shift |
| Final Drive | Sealed chain |
| | |

| Rear Tire | 130/80-18 |
|--------------|---|
| Front Brakes | Single 320mm petal-style disc with 2-piston calipers, ABS |
| Rear Brakes | Single 270mm petal-style disc with 2-piston caliper, ABS |

DETAILS

| | Frame Type | Double-cradle high tensile steel |
|-----|---------------------|----------------------------------|
| (2) | Rake/Trail | 26.0 / 3.7 in |
| | Overall Length | 86.2 in |
| | Overall Width | 31.1 in |
| | Overall Height | 42.3 in |
| | Ground Clearance | 4.9 in |
| | Seat Height | 31.1 in |
| 1 | Curb Weight | 496.1 lb.* |
| | Fuel Capacity | 4.0 gal |
| | Wheelbase | 57.7 in |
| | Color Choices | Metallic Ocean Blue |
| | Warranty | 12 month limited warranty |
| | | |

PERFORMANCE

| Front Suspension / Wheel Travel | 41mm telescopic fork with/5.1 in |
|---------------------------------------|--|
| Rear Suspension / Wheel Travel | Twin shocks with spring preload adjustability/4.2 in |
| Front Tire | 100/90-19 |

Scan with camera to view videos, key features and more.



*Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied). KAWASAKI CARES: Read Owner's Manual and all on-product warnings. Always wear a helmet, eye protection and proper apparel. Never ride under the influence of drugs or alcohol. Adhere to the maintenance schedule in your Owner's Manual. ©2025 Kawasaki Motors Corp., U.S.A. Specifications subject to change. Visit hawaii.kawasaki.com for full product details.