

2021

CONCOURS®14 ABS




 METALLIC SPARK BLACK



POWER		Front Tire	120/70 ZR-17
Engine	4-stroke, 4-cylinder, DOHC, 4-valve, liquid-cooled	Rear Tire	190/50 ZR-17
Displacement	1,352cc	Front Brakes	Dual floating 310mm petal-style discs with four-piston calipers, ABS
Bore x Stroke	84.0 x 61.0mm	Rear Brakes	Single 270mm petal-style disc, single-piston caliper, ABS
Compression Ratio	10.7:1	DETAILS	
Maximum Torque	100.5 lb-ft	Frame Type	Monocoque Aluminum
Fuel System	DFI® with 40mm throttle bodies (4)	Rake/Trail	26.0/4.4 in
Ignition	TCBI with electronic advance	Overall Length	87.8 in
Transmission	6-speed	Overall Width	31.1/39.4 wo/w saddlebags
Final Drive	Tetra-Lever shaft drive	Overall Height	52.9 in/57.7 in (windshield down/up)
Electronic Rider Aids	Kawasaki Advanced Coactive-Braking Technology (K-ACT) ABS System, Kawasaki Traction Control (KTRC)	Ground Clearance	4.9 in
PERFORMANCE		Seat Height	32.1 in
Front Suspension / Wheel Travel	43mm inverted, telescopic fork with adjustable rebound damping and spring preload/4.4 in	Curb Weight	690.2 lb (672.5 w/o saddlebags)*
Rear Suspension / Wheel Travel	Tetra-Lever with stepless rebound damping adjustment and remote spring preload adjuster/5.4 in	Fuel Capacity	5.8 gal
		Wheelbase	59.8 in
		Special Features	Electrically adjusted windshield
		Color Choices	Metallic Spark Black
		Warranty	36 Month Limited Warranty

Scan with camera to view videos, key features and more.



*Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied). KAWASAKI CARES: Read Owner's Manual and all on-product warnings. Always wear a helmet, eye protection and proper apparel. Never ride under the influence of drugs or alcohol. Adhere to the maintenance schedule in your Owner's Manual. ©2025 Kawasaki Motors Corp., U.S.A. Specifications subject to change. Visit hawaii.kawasaki.com for full product details.