²⁰²¹ KLX[®]230 ABS







4.10 x 18

POWER

TOWER		Front Brakes	Single 265mm petal disc with a dual-
Engine	4-stroke single, SOHC, air-cooled		piston caliper with Dual Purpose ABS
Displacement	233cc	Rear Brakes	Single 220mm petal disc with single- piston caliper with Dual Purpose ABS
Bore x Stroke	67.0 x 66.0mm	DETAILS	
Compression Ratio	9.4:1		
Fuel System	DFI® with 32mm Keihin throttle body	Frame Type	High-tensile steel, box-section perimeter
Ignition	TCBI Electronic Advance	Rake/Trail	27.5°/4.6 in
Transmission	6-speed, return shift with wet multi-disc	Overall Length	82.9 in.
mansiinssion	manual clutch	Overall Width	32.9 in.
Final Drive	Chain	Overall Height	45.9 in.
PERFORMANCE		Ground Clearance	10.4 in.
Front	37mm telescopic fork/8.7 in	Seat Height	34.8 in.
Suspension / Wheel Travel		Curb Weight	293.3 lb. / 295.5 lb. CA model*
Rear	Uni-Trak [®] linkage system and single shock	Fuel Capacity	2.0 gal.
Suspension / Wheel Travel	with adjustable spring preload/8.8 in	Wheelbase	54.3 in.
Front Tire	2.75 x 21	Color Choices	Lime Green

Rear Tire



*Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied). KAWASAKI CARES: Read Owner's Manual and all on-product warnings. Always wear a helmet, eye protection and proper apparel. Never ride under the influence of drugs or alcohol. Adhere to the maintenance schedule in your Owner's Manual. ©2025 Kawasaki Motors Corp., U.S.A. Specifications subject to change. Visit hawaii.kawasaki.com for full product details.

12 Months

Warranty