## **MULE**<sup>™</sup> 4010 4x4<sup>®</sup> FE







D	N	V	V	C	D
Г	u	ľ	V	г	π

Engine 4-stroke, 2-cylinder, OHV, 90° V Liquid-cooled

Displacement 617cc

Maximum Torque 34.7 lb-ft @ 2500 rpm

Bore x Stroke 2.99x2.68 in

Compression Ratio 10:3:

Fuel System DFI® with 34mm Mikuni throttle body

Transmission Continuously Variable Transmission (CVT) with (H,L,N,R)

Final Drive Selectable 2WD/4WD, shaft. Dual mode rear differential

with differential lock

Engine Braking N

Alternator Output

(max)

23 amp

## **CAPABILITY**

Front Suspension / MacPherson Strut/3.9 in Wheel Travel

Rear Suspension / Wheel Travel DeDion Axle/2.8 in

Front Tires 23x11.00-10

Rear Tires 23x11.00-10

Steering Electric Power Steering (EPS)

Park Brake Type Independent, Mechanical Drum

Front Brakes Drum

Rear Brakes Drum

**Ground Clearance** 6.9 in

Fuel Capacity 6.3 gal

Turning Radius 11.2 ft

Dimensions (LxWxH)

Cargo Bed Load

Capacity

**Cargo Bed** 

800 lb

Payload Capacity 1327 lb

Seating Capacity 2

Towing Capacity 1200 lb

Lighting (2) Halogen headlights (2) tail/brake lights

46.3 x 51.6 x 11.4 in

## **DETAILS**

Overall Length 116.7 in

Overall Width 62.0 in

Overall Height 78.1 in

Curb Weight 1448.7 lb\*

Wheelbase 73.6 in

**Instruments** Parking brake warning light, coolant temperature

warning light, horn, 12V DC outlet, fuel gauge, hour

meter

Wheel Type Steel

Color Choices Bright White

Warranty Kawasaki 3-Year Limited Warranty



