MULE PRO-DX™ EPS DIESEL







P	N	V	V	F	R

Engine 4-stroke, 3-cylinder, OHV, liquid-cooled, diesel

Displacement 993cc

Maximum Torque 38.3 lb-ft @ 2400 rpm

Bore x Stroke 2.91x3.03 in

Compression Ratio 23.5:1

Fuel System Bosch in-line injection pump

Continuously Variable Transmission (CVT) with (H,L,N,R) Transmission

Final Drive Selectable 2WD/4WD, shaft. Dual mode rear differential

with differential lock

Engine Braking

Alternator Output 55 amp

(max)

Ground Clearance 10.4 in

Fuel Capacity 7.9 gal **Turning Radius**

Cargo Bed 54.1 x 53.3 x 11.0 in

Dimensions (LxWxH)

Cargo Bed Load

Capacity

Payload Capacity

Seating Capacity

Towing Capacity 2000 lb

Lighting (2) Halogen headlights.

16.0 ft

1000 lb

1581 lb

CAPABILITY

Front Suspension / **Wheel Travel**

Double wishbone/8.7 in

Rear Suspension / **Wheel Travel**

Double wishbone/8.5 (L) /8.7 (R) in

Front Tires 26x9.00-12 **Rear Tires** 26x11.00-12

Electric Power Steering (EPS), Tilt steering Steering

Park Brake Type Independent, Mechanical Disc **Front Brakes** Dual Disc, 2 piston caliper

Rear Brakes Dual Disc, 1 piston caliper

DETAILS

Overall Length 133.3 in

Overall Width 64.0 in

Overall Height 77.4 in

Curb Weight 1852.2 lb*

Wheelbase 92.3 in

Instruments Multi-function display includes digital speedometer,

fuel gauge, odometer, hour meter, clock, dual trip meters, 2WD/4WD indicator, water temperature warning indicator, oil pressure warning indicator, glow plug indicator, CVT and EPS warning indicators, neutral, reverse and parking indicators, seatbelt reminder lamps

Wheel Type

Color Choices Timberline Green

Kawasaki 3-Year Limited Warranty Warranty

Scan with camera to view videos, key features and more.

