
MULE PRO-FXR™









POWER

Engine 4-stroke, 3-cylinder, DOHC, liquid-cooled, gas

Displacement 812cc

Maximum Torque 48.0 lb-ft @ 3500 rpm

Bore x Stroke 2.83 x 2.62 in

Compression Ratio 9.5:

Fuel System DFI® with 34mm throttle body

Transmission Continuously Variable Transmission (CVT) with (H,L,N,R)

Final Drive Selectable 2WD/4WD, shaft. Dual mode rear differential

with differential lock

Engine Braking Ye

Alternator Output

(max)

. . . .

75 amp

CAPABILITY

Front Suspension / Double wishbone / 8.7 in Wheel Travel

Rear Suspension /

Double wishbone/8.5 (L) /8.7 (R) in

Wheel Travel
Front Tires

27x9.00-12, radial

Rear Tires 27x11.00-12, radial

Steering Electric Power Steering (EPS), Tilt steering

Park Brake Type

Independent, Mechanical Disc

Front Brakes

Dual Disc, 2 piston caliper

Rear Brakes

Dual Disc, 1 piston caliper

Ground Clearance 10.8 in

Fuel Capacity 7.9 gal

Turning Radius 14.0 ft

Cargo Bed Dimensions 37.6 x 53.3 x 11.0 in

(LxWxH)

1000 lb (600 lb for California models)

Capacity

Cargo Bed Load

Payload Capacity 1616 lb

Seating Capacity 3

Towing Capacity 2000 lb

Lighting (2) Halogen headlights. (2) LED headlights

DETAILS

Overall Length 121.5 in

Overall Width 64.0 in

Overall Height 77.2 in

Curb Weight 1768.4 lb*

Wheelbase 79.7 in

Instruments Multi-function display includes digital speedometer,

fuel gauge, odometer, hour meter, clock, dual trip meters, 2WD/4WD indicator, water temperature warning indicator, oil pressure warning indicator, fuel injection warning indicator, CVT and EPS warning indicators, neutral, reverse and parking indicators,

seatbelt reminder lamps

Color Choices Metallic Carbon Gray, Candy Persimmon Red

Warranty Kawasaki 3-Year Limited Warranty



