

2021

MULE SX™ 4x4 XC CAMO FI



POWER

Engine	4-stroke, single-cylinder, OHV, air-cooled
Displacement	401cc
Maximum Torque	21.4 lb-ft @ 2400 rpm
Bore x Stroke	3.23x2.99 in
Compression Ratio	8.6:1
Fuel System	Fuel injection
Transmission	Continuously Variable Transmission (CVT) with (H,L,N,R)
Final Drive	Selectable 2WD/4WD, shaft. Dual mode rear differential with differential lock
Engine Braking	No
Alternator Output (max)	22.9 amp

CAPABILITY

Front Suspension / Wheel Travel	MacPherson Strut/3.1 in
Rear Suspension / Wheel Travel	Unit Swingarm/3.1 in
Front Tires	26x9.00-12
Rear Tires	26x9.00-12
Steering	Rack-and-pinion, Tilt steering
Park Brake Type	Independent, Mechanical Drum
Front Brakes	Drum

Rear Brakes	Drum
Ground Clearance	8.1 in
Fuel Capacity	4.2 gal
Turning Radius	11.8 ft
Cargo Bed Dimensions (LxWxH)	35.6 x 40.9 x 9.6 in
Cargo Bed Load Capacity	400 lb
Payload Capacity	884 lb
Seating Capacity	2
Towing Capacity	1100 lb*
Lighting	(2) LED headlights, tail/brake lights

DETAILS

Overall Length	106.7 in
Overall Width	52.6 in
Overall Height	73.4 in
Curb Weight	1098.1 lb**
Wheelbase	70.1 in
Instruments	Fuel gauge, hour meter oil temp light, parking brake light
Color Choices	Realtree Xtra® Green Camo
Warranty	Kawasaki 3-Year Limited Warranty



\*Requires Optional Hitch  
\*Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied).  
KAWASAKI CARES: Read Owner's Manual and all on-product warnings. Always wear protective gear appropriate for the use of this vehicle. Never operate under the influence of drugs or alcohol. Protect the environment. The Kawasaki MULE™ side x side is an off-highway vehicle only, and is not designed, equipped or manufactured for use on public streets, roads or highways. Obey the laws and regulations that control the use of your vehicle. ©2025 Kawasaki Motors Corp., U.S.A. Specifications subject to change. Visit hawaii.kawasaki.com for full product details.