





	_			
P	n	м	V	n
Р		W	w I	к
				-

Engine 2-stroke single, liquid-cooled

Displacement 64cc

Bore x Stroke 45.5 x 41.6mm

Compression

Ratio

8.4:1

24mm Mikuni carburetor **Fuel System**

Ignition

Transmission 6-speed, return shift, with wet multi-disc

manual clutch

Final Drive Chain

CDI with digital advance

PERFORMANCE

33mm leading axle telescopic fork with 4-**Front** Suspension / way rebound damping/8.3 in **Wheel Travel**

> Uni-Trak® single shock system with stepless 3-turns rebound damping and fully adjustable spring preload/9.4 in

Front Tire 60/100-14 **Rear Tire** 80/100-12

Single 180mm disc with single-piston **Front Brakes**

caliper

Rear Brakes Single 180mm disc with single-piston

caliper

12.0 in

DETAILS

High-tensile steel semi-double cradle **Frame Type**

27°/2.4 in Rake/Trail

Overall Length 62.6 in

Overall Width 29.9 in

Overall Height 37.6 in

Clearance

Ground

Seat Height 29.9 in

Curb Weight 132.2 lb*

Fuel Capacity 1.0 gal

Wheelbase 44.1 in

Color Choices Lime Green

Not Available Warranty



Rear

Suspension /

Wheel Travel

