MULE PRO-FX™ EPS









POWER

Engine 4-stroke, 3-cylinder, DOHC, liquid-cooled, gas

Displacement 812cc

Maximum Torque 48.0 lb-ft @ 3,500 rpm

Bore x Stroke 2.83x2.62 in

Compression Ratio 9.5:

Fuel System DFI® with 34mm throttle body

75 amp

Transmission Continuously Variable Transmission (CVT) with (H,L,N,R)

Final Drive Selectable 2WD/4WD, shaft. Dual mode rear differential

with differential lock

Engine Braking Ye

Alternator Output

(max)

Fuel Capacity 7

Ground Clearance

Fuel Capacity 7.9 gal

Turning Radius 16.0 ft

Cargo Bed Dimensions

(LxWxH)

54.1 x 53.3 x 11.0 in

10.4 in

Cargo Bed Load

Capacity

999 lb / 600.0 lb CA Model

Payload Capacity

1,616.3 lb / 1,263.5 for CA Model

Seating Capacity

Towing Capacity 2,000 lb

Lighting (2) Halogen headlights.

CAPABILITY

Front Suspension / Double wishbone / 8.7 in Wheel Travel

Rear Suspension / Double wishbone/8.5 in (L) /8.7 in (R)

Front Tires 26x9.00-12, radial
Rear Tires 26x11.00-12, radial

Steering Electric Power Steering (EPS), Tilt steering

Park Brake Type Independent, Mechanical Disc

Front Brakes Dual Disc, 2 piston caliper

Rear Brakes Dual Disc, 1 piston caliper

Dual Disc, 2 piston caliper Color Ch

DETAILS

Overall Length 133.3 in

Overall Width 64.0 in

Overall Height 77.4 in

Curb Weight 1,830.2 lb*

Wheelbase 92.3 in

Instruments Multi-function display includes digital speedometer,

fuel gauge, odometer, hour meter, clock, dual trip meters, 2WD/4WD indicator, water temperature warning indicator, oil pressure warning indicator, fuel injection warning indicator, CVT and EPS warning indicators, neutral, reverse and parking indicators,

seatbelt reminder lamps

Color Choices Timberline Green, Bright White

Warranty Kawasaki STRONG 3-Year Limited Warranty

Scan with camera to view videos, key features and more.

