VULCAN® 1700 VAQUERO® ABS







POWER	
Engine	4-stroke, 52-degree V-twin, liquid-cooled
Displacement	1,700cc/103.7 cu in
Bore x Stroke	102.0 x 104.0mm
Compression Ratio	9.5:1
Maximum Torque	107.6 lb-ft @ 2,750 rpm
Fuel System	DFI® with 42mm throttle bodies (2)
Ignition	TCBI with Electronic Advance

PERFORMANCE		
Electronic Rider Aids	Electronic Cruise Control, Kawasaki Advanced Coactive-Braking Technology (K-ACT) ABS	
Final Drive	Carbon fiber-reinforced belt	
Transmission	6-speed with overdrive and positive neutral finder	
Ignition	TCBI with Electronic Advance	
Fuel System	DFI® with 42mm throttle bodies (2)	
Maximum Torque	107.6 lb-ft @ 2,750 rpm	
Compression Ratio	9.5:1	

DFI® with 42mm throttle bodies (2)
TCBI with Electronic Advance
6-speed with overdrive and positive neutral finder
Carbon fiber-reinforced belt
Electronic Cruise Control, Kawasaki Advanced Coactive-Braking Technology (K-ACT) ABS
Couctive Bruking recimology (K ACT/ABS
ANCE
ANCE

Rear Tire	170/70-16
Front Brakes	Dual 300mm discs, dual four-piston calipers, K-ACT ABS
Rear Brakes	Single 300mm disc, twin-piston caliper, K-ACT ABS

n	F 7	ГΑ	Ш	2.
ш		А	ш	
_	_			

Frame Type	Steel, double-cradle with box-section single-tube backbone	
Rake/Trail	30°/7.0 in	
Overall Length	98.8 in	
Overall Width	38.2 in	
Overall Height	50.8 in	
Ground Clearance	5.7 in	
Seat Height	28.7 in	
Curb Weight	844.5 lb*	
Fuel Capacity	5.3 gal	
Wheelbase	65.6 in	
Special Features	Integrated audio system with SiriusXM Radio compatibility	
Color Choices	Metallic Matte Twilight Blue	
Warranty	36 Month Limited Warranty	



