
VULCAN® 900 CUSTOM









Single 300mm hydraulic disc

Single 270mm hydraulic disc

POWER

Engine 4-stroke, 55-degree V-twin, liquid-cooled

Displacement 903cc/55.10 cu in

9.5:1

Bore x Stroke 88.0 x 74.2mm

Compression

Ratio

Maximum

Torque

58.2 lb-ft @ 3,500 rpm

Fuel System DFI® with 34mm throttle bodies (2), with sub-

throttle valves

Ignition TCBI with Electronic Advance

Transmission 5-speed with positive neutral finder

Final Drive Kevlar-reinforced belt

DETAILS

Rear Tire

Front Brakes

Rear Brakes

Frame Type Semi-double cradle, high-tensile steel

180/70-15

Rake/Trail 33°/7.2 in

Overall Length 94.7 in

Overall Width 35.2 in

Overall Height 44.1 in

Ground 5.5 in Clearance

Seat Height 27.0 in

Curb Weight 610.8 lb*

Fuel Capacity 5.3 gal

Wheelbase 64.8 in

Color Choices Metallic Matte Dark Gray/Metallic Flat Spark

Black

Warranty 12 Month Limited Warranty

Kawasaki 12, 24, 36, or 48 months Protection

PERFORMANCE

Suspension / Wheel Travel 41mm Showa telescopic fork/5.9 in

Rear Suspension / Wheel Travel

Uni-Trak® swingarm, 7-way adjustable spring preload/4.1 in

Front Tire

80/90-21





Plus™ (optional)