## **VULCAN® 900 CUSTOM**









## **POWER**

Engine 4-stroke, 55-degree V-twin, liquid-cooled

**Displacement** 903cc/55.10 cu in

Bore x Stroke 88.0 x 74.2mm

Compression 9.5:1

Ratio

Maximum Torque 58.2 lb-ft @ 3,500 rpm

**Fuel System** 

DFI® with 34mm throttle bodies (2), with

sub-throttle valves

Ignition

TCBI with Electronic Advance

**Transmission** 

5-speed with positive neutral finder

**Final Drive** 

Kevlar-reinforced belt

## **PERFORMANCE**

Front
Suspension /
Wheel Travel

41mm Showa telescopic fork/5.9 in

Rear Suspension / Wheel Travel Uni-Trak® swingarm, 7-way adjustable

spring preload/4.1 in

**Front Tire** 80/90-21

**Rear Tire** 180/70-15

Front Brakes Single 300mm hydraulic disc

**Rear Brakes** Single 270mm hydraulic disc

## **DETAILS**

Frame Type Semi-double cradle, high-tensile steel

Rake/Trail 33° /7.2 in

Overall Length 94.7 in

Overall Width 35.2 in

Overall Height 44.1 in

Ground 5.5 in Clearance

Seat Height 27.0 in

Curb Weight 610.8 lb\*

Fuel Capacity 5.3 gal

Wheelbase 64.8 in

**Color Choices** Metallic Matte Dark Gray/Metallic Flat

Spark Black

**Warranty** 12 Month Limited Warranty



