

2024

# Z900RS SE ABS



 METALLIC DIABLO BLACK



POWER		Rear Tire	180/55 ZR17
Engine	4-stroke, 4-cylinder, DOHC, 16-valve, liquid-cooled	Front Brakes	Dual 300mm discs with Brembo M4.32 monobloc four-piston calipers, ABS
Displacement	948cc	Rear Brakes	Single 250mm disc with single-piston caliper, ABS
Bore x Stroke	73.4 x 56.0mm	DETAILS	
Compression Ratio	10.8:1	Frame Type	Trellis, high tensile steel
Maximum Torque	72.3 lb-ft @ 6,500 rpm	Rake/Trail	25.0° / 3.9 in
Fuel System	DFI® with Keihin 36mm throttle bodies	Overall Length	83.1 in
Ignition	TCBI with Electronic Advance	Overall Width	34.1 in
Transmission	6-speed, return shift	Overall Height	46.5 in
Final Drive	Sealed chain	Ground Clearance	5.1 in
Electronic Rider Aids	Economical Riding Indicator, Kawasaki TRaction Control (KTRC - 3 Modes), Anti-lock Brake System (ABS)	Seat Height	32.9 in
PERFORMANCE		Curb Weight	471.9 lb* 50-State Model
Front Suspension / Wheel Travel	Inverted telescopic fork with (13-way) adjustable compression and rebound (11-way) damping, spring preload (15-turn)/4.7	Fuel Capacity	4.5 gal
Rear Suspension / Wheel Travel	Horizontal back-link swingarm, Ohlins shock with 30-position adjustable rebound damping and stepless spring preload adjustability/5.5 in	Wheelbase	57.9 in
Front Tire	120/70 ZR17	Color Choices	Metallic Diablo Black
		Warranty	12 Month Limited Warranty
		Kawasaki Protection Plus™ (optional)	12, 24, 36, or 48 months

Scan with camera to view videos, key features and more.



\*Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied). KAWASAKI CARES: Read Owner's Manual and all on-product warnings. Always wear a helmet, eye protection and proper apparel. Never ride under the influence of drugs or alcohol. Adhere to the maintenance schedule in your Owner's Manual. ©2024 Kawasaki Motors Corp., U.S.A. Specifications subject to change. Visit [hawaii.kawasaki.com](http://hawaii.kawasaki.com) for full product details.