Z900RS ABS







P	N	V	N	F	R
•	u	Д.		_	

Engine 4-stroke, 4-cylinder, DOHC, 16-valve, liquid-

cooled

Displacement 948cc

Bore x Stroke 73.4 x 56.0mm

Compression

Ratio

10.8:1

Maximum Torque 72.3 lb-ft @ 6,500 rpm

Fuel System DFI® with Keihin 36mm throttle bodies

Ignition TCBI with Electronic Advance

Transmission 6-speed, return shift

Final Drive Sealed chain

Electronic Rider

Aids

Economical Riding Indicator, Kawasaki TRaction Control (KTRC - 3 Modes), Anti-lock Brake

System (ABS)

PERFORMANCE

Front
Suspension /
Wheel Travel

Inverted telescopic fork with (13-way) adjustable compression and rebound (11-way) damping, spring preload (15-turn)/4.7

Rear Suspension / Wheel Travel

Horizontal back-link swingarm with stepless adjustable rebound damping and spring

preload/5.5 in

Front Tire 120/70 ZR17

Rear Tire 180/55 ZR17

Front Brakes Dual 300mm discs with four-piston calipers,

ABS

Rear Brakes Single 250mm disc with single-piston caliper,

ABS

DETAILS

Frame Type Trellis, high tensile steel

Rake/Trail 25.0°/3.9 in

Overall Length 82.7 in

Overall Width 34.1 in

Overall Height 45.3 in

Ground 5.1 in

Clearance

Seat Height 32.9 in

Curb Weight 471.9 lb* 50-State Model

Fuel Capacity 4.5 gal

Wheelbase 57.9 in

Color Choices Metallic Diablo Black

Warranty 12 Month Limited Warranty

Kawasaki 12, 24, 36, or 48 months Protection





Plus™ (optional)