

2024

JET SKI® ULTRA® 160LX-S

Kawasaki

Let the Good Times Roll®

EBONY/CANDY STEEL FURNACE ORANGE

POWER		PERFORMANCE	
Engine	4-stroke, DOHC, four valves per cylinder, 4-cylinder inline	Lubrication	Semi-dry sump system
Displacement	1,498cc	Coupling	Direct drive from engine
Bore x Stroke	83.0 x 69.2mm	Oil Capacity	5.8 qt
Compression Ratio	10.6:1	Fuel Capacity	21.1 gal
Induction	Naturally aspirated	Load Capacity	496 lb
Maximum Boost	N/A	Storage Capacity	44.5 gal
Cooling System	Inducted water	DETAILS	
Fuel System	DFI® with 60mm throttle body	Overall Length	140.9 in
Ignition	TCBI with Digital Advance	Overall Width	47.0 in
Starting System	Electric	Overall Height	46.5 in
Propulsion System	155mm jet pump, axial-flow, single stage	Curb Weight	963.6 lb*
Impeller	3-blade, oval-edge stainless steel	Seating Capacity	3
		Color Choices	Ebony/Candy Steel Furnace Orange
		Warranty	12 Month Limited Warranty

Scan with camera to view videos, key features and more.

\*Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied). KAWASAKI CARES: Ride responsibly. Kawasaki believes safety begins with us and continues with you. Always wear a USCG-approved personal flotation device, eyewear, gloves, footwear, and a wet suit or clothing that provides equivalent protection (board shorts with neoprene liner). Never ride under the influence of drugs or alcohol. Respect the rights of shoreline residents and other marine recreationists. Boat smart from the start. Take a Boating Safety course; for more information visit [www.USCGBoating.org](http://www.USCGBoating.org). Jet Ski watercraft are inboard powerboats and their use is subject to all applicable federal, state, and local boating laws. Read Owner's Manual and all on-product warnings. ©2025 Kawasaki Motors Corp., U.S.A. Specifications subject to change. Visit [hawaii.kawasaki.com](http://hawaii.kawasaki.com) for full product details.