## JET SKI® ULTRA® 310LX-S





EBONY/LIME GREEN



Impeller

3-blade, oval-edge stainless steel

## POWER

Engine	Supercharged and intercooled, 4-stroke, DOHC, four valves per cylinder, inline 4- cylinder
Displacement	1,498cc
Bore x Stroke	83.0 x 69.2mm
Compression Ratio	8.2:1
Induction	Eaton Twin Vortices Series Roots-type supercharger with air-to-water intercooler
Maximum Boost	16.8 psi
Cooling System	Inducted water
Fuel System	DFI® with 60mm throttle body
Ignition	TCBI with Digital Advance
Starting System	Electric
Propulsion System	160mm jet pump, axial-flow, single stage

## PERFORMANCE

Lubrication	Semi-dry sump system
Coupling	Direct drive from engine
Oil Capacity	5.3 qt
Fuel Capacity	21.1 gal
Load Capacity	496 lb
Storage Capacity	44.5 gal

## DETAILS

<b>Overall Length</b>	140.9 in
Overall Width	47.0 in
Overall Height	46.5 in
Curb Weight	1,065.0 lb*
Seating Capacity	3
<b>Color Choices</b>	Ebony/Lime Green
Warranty	12 Month Limited Warranty





\*Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied). KAWASAKI CARES: Ride responsibly. Kawasaki believes safety begins with us and continues with you. Always wear a USCG-approved personal flotation device, eyewear, gloves, footwear, and a wet suit or clothing that provides equivalent protection (board shorts with neoprene liner). Never ride under the influence of drugs or alcohol. Respect the rights of shoreline residents and other marine recreationists. Boat smart from the start. Take a Boating Safety course; for more information visit www.USCGBoating.org. Jet Ski® watercraft are inboard powerboats and their use is subject to all applicable federal, state, and local boating laws. Read Owner's Manual and all on-product warnings. ©2025 Kawasaki Motors Corp., U.S.A.

Specifications subject to change. Visit hawaii.kawasaki.com for full product details.