


2024

KLX<sup>®</sup>230SM ABS



 BATTLE GRAY



POWER

Engine	4-stroke single, SOHC, air-cooled
Displacement	233cc
Bore x Stroke	67.0 x 66.0mm
Compression Ratio	9.4:1
Maximum Torque	13.2 lb-ft @ 6,400 rpm
Fuel System	DFI <sup>®</sup> with dual 32mm throttle bodies
Ignition	TCBI with Electronic Advance
Transmission	6-speed
Final Drive	Sealed chain
Electronic Rider Aids	Anti-lock Brake System (ABS)

PERFORMANCE

Front Suspension / Wheel Travel	37mm inverted fork/7.4 in
Rear Suspension / Wheel Travel	Uni-Trak <sup>®</sup> linkage system and single shock with adjustable spring preload/8.7 in
Front Tire	110/70-17
Rear Tire	120/70-17

Front Brakes	Single 300mm petal disc with a dual-piston caliper and ABS
Rear Brakes	Single 220mm petal disc with single-piston caliper and ABS

DETAILS

Frame Type	Perimeter, high-tensile steel
Rake/Trail	24.9° /3.0 in
Overall Length	80.1 in
Overall Width	33.2 in
Overall Height	44.2 in
Ground Clearance	8.6 in
Seat Height	33.0 in
Curb Weight	299.8/302.0 lb* 50-State Model
Fuel Capacity	2.0 gal
Wheelbase	53.7 in
Special Features	ERGO-FIT <sup>®</sup> , LCD Instrumentation with Smartphone Connectivity via RIDELOGY THE APP MOTORCYCLE
Color Choices	Battle Gray
Warranty	12 Month Limited Warranty

Scan with camera to view videos, key features and more.



\*Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied). KAWASAKI CARES: Read Owner's Manual and all on-product warnings. Always wear a helmet, eye protection and proper apparel. Never ride under the influence of drugs or alcohol. Adhere to the maintenance schedule in your Owner's Manual. ©2025 Kawasaki Motors Corp., U.S.A. Specifications subject to change. Visit [hawaii.kawasaki.com](http://hawaii.kawasaki.com) for full product details.