# KLX®300R









### **POWER**

4-stroke single, DOHC, liquid-cooled **Engine** 

**Displacement** 292cc

**Bore x Stroke** 78.0 x 61.2mm

Compression

Ratio

11.1:1

**Fuel System** DFI® with 34mm Keihin throttle body

**Transmission** 6-speed, return shift with wet multi-disc

manual clutch

**Final Drive** Chain

### Ignition TCBI Electronic Advance

## **PERFORMANCE**

43mm inverted telescopic fork with **Front** Suspension / adjustable compression damping /11.2 in **Wheel Travel** 

Uni-Trak® gas charged shock with piggyback Rear reservoir with adjustable compression, Suspension / **Wheel Travel** rebound damping and spring preload/11.2 in

**Front Tire** 3.0 x 21

**Rear Tire** 4.6 x 18 **Front Brakes** Single 270mm petal disc with a dual-piston caliper

**Rear Brakes** Single 240mm petal disc with single-piston

# **DETAILS**

Semi-Double Cradle **Frame Type** 

26.9° / 4.3 in Rake/Trail

**Overall Length** 86.6 in

**Overall Width** 32.5 in

**Overall Height** 49.0 in

Ground 11.8 in

Clearance

Plus™ (optional)

**Seat Height** 35.4 in

**Curb Weight** 282.2 lb\* / 286.7 lb\* CA Model

**Fuel Capacity** 2.1 gal

Wheelbase 56.5 in

**Color Choices** Lime Green, Battle Gray

6 Months Warranty

Kawasaki 12, 24, or 36 months **Protection** 



