





POWER			
Engine	4-stroke single, DOHC, liquid-cooled		
Displacement	249cc		
Bore x Stroke	78.0 x 52.2mm		
Compression Ratio	14.1:1		
Fuel System	DFI® with 44mm Keihin throttle body and dual injectors		
Ignition	Digital CDI		

Ratio	
Fuel System	DFI® with 44mm Keihin throttle body and dual injectors
Ignition	Digital CDI
Transmission	5-speed, return shift, with wet multi-disc manual clutch
Final Drive	Chain
Electronic Rider Aids	Launch Control Mode

PERFORMANCE

Front Suspension / Wheel Travel	48mm inverted telescopic coil-spring fork with 23-way compression damping and 20-way rebound damping /12.4 in
Rear Suspension / Wheel Travel	Uni-Trak® with dual-range (2.25 turns high speed/21-way low-speed) compression damping, 38-way rebound damping and adjustable preload/12.4 in
Front Tire	80/100-21

Rear Tire	110/90-19
Front Brakes	Single semi-floating 270mm Braking petal disc with dual-piston caliper
Rear Brakes	Single 240mm Braking petal disc with single- piston caliper

n	67	ΓA	Ш	S
ш		Δ	ш	-7
_				

Frame Type	Aluminum perimeter
Rake/Trail	28.0°/4.6 in
Overall Length	86.2 in
Overall Width	32.3 in
Overall Height	50.0 in
Ground Clearance	13.6 in
Seat Height	37.8 in
Curb Weight	227.6 lb* without fuel / 237.7 lb*
Fuel Capacity	1.64 gal
Wheelbase	58.5 in
Color Choices	Lime Green
Warranty	Not Available
Kawasaki Protection Plus™ (optional)	Not Available



