





P	N	V	V	F	D
Г	u	V	v	Г	π

Engine 4-stroke single, DOHC, liquid-cooled

Displacement 249cc

Bore x Stroke 78.0 x 52.2mm

Compression

Ratio

14.1:1

DFI® with 44mm Keihin throttle body and **Fuel System**

dual injectors

Ignition Digital CDI

Transmission 5-speed, return shift, with wet multi-disc

manual clutch

Final Drive Chain

Electronic Rider

Aids

Launch Control Mode

PERFORMANCE

Front Suspension / **Wheel Travel** 48mm inverted telescopic coil-spring fork with 23-way compression damping and 20way rebound damping /12.4 in

Rear Suspension / **Wheel Travel**

Uni-Trak® with dual-range (2.25 turns high speed/21-way low-speed) compression damping, 38-way rebound damping and adjustable preload/12.4 in

Front Tire 80/100-21

Rear Tire 110/90-19

Front Brakes Single semi-floating 270mm Braking petal

disc with dual-piston caliper

Rear Brakes Single 240mm Braking petal disc with

single-piston caliper

DETAILS

Aluminum perimeter **Frame Type**

28.0°/4.6 in Rake/Trail

Overall Length 86.2 in

Overall Width 32.3 in

Overall Height 50.0 in

Ground 13.6 in Clearance

Seat Height 37.8 in

Curb Weight 227.6 lb* without fuel / 237.7 lb*

Fuel Capacity 1.64 gal

Wheelbase 58.5 in

Color Choices Lime Green

Not Available Warranty



