## **KX**<sup>™</sup>250X









## **POWER**

**Engine** 4-stroke single, DOHC, liquid-cooled

Displacement 249cc

Bore x Stroke 78.0 x 52.2mm

Compression

Ratio

14.1:1

Fuel System DFI® with 44mm Keihin throttle body and

dual injectors

**Ignition** Digital CDI

**Transmission** 5-speed, return shift, with wet multi-disc

manual clutch

Final Drive Chain

**Electronic Rider** 

**Aids** 

Cilaiii

Launch Control Mode

Laurich Control Mode

## **PERFORMANCE**

Front
Suspension /
Wheel Travel

48mm inverted telescopic coil-spring fork with 23-way compression damping and 20-way rebound damping/12.4 in

Rear Suspension / Wheel Travel Uni-Trak® with dual-range (2.25 turns high speed/21-way low-speed) compression damping, 38-way rebound damping and

adjustable preload/12.4 in

Front Tire 80/100-21

**Rear Tire** 110/100-18

Front Brakes Single semi-floating 270mm Braking petal

disc with dual-piston caliper

**Rear Brakes** Single 240mm Braking petal disc with

single-piston caliper

## **DETAILS**

Frame Type Aluminum perimeter

Rake/Trail 27.8°/4.8 in

Overall Length 85.4 in

Overall Width 32.3 in

Overall Height 49.6 in

Ground 13.0 in Clearance

Seat Height 37.2 in

Curb Weight 230.1 lb\* without fuel / 240.2 lb\*

Fuel Capacity 1.64 gal

Wheelbase 58.3 in

**Color Choices** Lime Green

Warranty Not Available

Scan with camera to view videos, key features and more.

