





80/100-12

caliper

caliper

12.0 in

	~		FR
u			LU
		-	-

Engine 2-stroke single, liquid-cooled

Displacement 64cc

Bore x Stroke 44.5 x 41.6mm

Compression

Ratio

8.4:1

Fuel System 24mm Mikuni carburetor

Ignition CDI with Digital Advance

Transmission 6-speed, return shift, with wet multi-disc

manual clutch

Final Drive Chain

DETAILS

Rear Tire

Front Brakes

Rear Brakes

Frame Type High-tensile steel semi-double cradle

Single 180mm disc with single-piston

Single 180mm disc with single-piston

Rake/Trail 27°/2.4 in

Overall Length 62.6 in

Overall Width 29.9 in

Overall Height 37.6 in

Clearance

Ground

Seat Height 29.9 in

Curb Weight 132.2 lb*

Fuel Capacity 1.0 gal

Wheelbase 44.1 in

Color Choices Lime Green

Warranty Not Available

PERFORMANCE

Front
Suspension /
Wheel Travel

33mm leading axle telescopic fork with 4way rebound damping/8.3 in

Rear Suspension / Wheel Travel Uni-Trak® single shock system with stepless 3-turns rebound damping and fully adjustable spring preload/9.4 in

Front Tire

60/100-14



