





D	N	I	M		D
Г	u	V.	ľ	E	П

2-stroke single with exhaust power valve (KIPS), liquid-cooled

Displacement 84cc

48.5 x 45.8mm

Compression

**Bore x Stroke** 

10.9:1 (low speed) / 9.0:1 (high speed)

Ratio

28mm Keihin carburetor

Fuel System

Ignition

CDI with Digital Advance

**Transmission** 

6-speed, return shift, with wet multi-disc

manual clutch

**Final Drive** 

Chain

## **PERFORMANCE**

Front
Suspension /
Wheel Travel

36mm inverted telescopic cartridge fork with 20-way compression damping/10.8 in

Rear Suspension / Wheel Travel Uni-Trak® single shock system with 24-way compression and 21-way rebound damping, plus adjustable spring preload/10.8 in

**Front Tire** 

70/100-17

Rear Tire 90/100-14

Front Brakes Single 220mm petal disc with dual-piston caliper

Rear Brakes Single 184mm petal disc with single-piston caliper

## **DETAILS**

High-tensile steel perimeter design with **Frame Type** subframe member 29° /3.8 in Rake/Trail **Overall Length** 72.0 in **Overall Width** 30.1 in **Overall Height** 43.3 in 11.4 in Ground Clearance **Seat Height** 32.7 in **Curb Weight** 164.4 lb\* **Fuel Capacity** 1.32 gal Wheelbase 49.8 in **Color Choices** Lime Green

Not Available





Warranty