MULE PRO-FXT™ 1000 LE CAMO







POWER

Engine 4-stroke, 2-cylinder, DOHC, liquid-cooled, gas

Displacement 999cc

Maximum Torque 61.5 lb-ft

Bore x Stroke 92.0 x 75.1mm

Compression Ratio 10.1:1

Fuel System DFI® with 38mm throttle body

Transmission Continuously Variable Transmission (CVT) with (L,H,N,R)

Final Drive Selectable 2WD/4WD, shaft Dual mode rear differential

with differential lock

Engine Braking

Alternator Output 90 amp

(max)

Ground Clearance 12.6 in (max), 11.6 in (std)

Fuel Capacity 7.9 gal

Turning Radius 16.0 ft

Cargo Bed

Dimensions (LxWxH)

person)

Cargo Bed Load

Payload Capacity

Capacity

1,616.3 lb / 1,263.5 lb CA Model

Seating Capacity

3-person (1 row), 6 person (2 row)

1,922.8 lb* / 1,925 lb* CA Model

Towing Capacity 2,000 lb

135.8 in

64.0 in

80.9 in

92.3 in

Lighting

DETAILS

Overall Length

Overall Width

Overall Height

Curb Weight

Wheelbase

(2) Halogen headlights. (2) LED headlights

42.7 x 53.7 x 11.0 in (3-person) / 22.0 x 53.7 x 11.0 in (6-

999 lb (3-person) / 350 lb (6-person) / 348 lb CA Model

CAPABILITY

Front Suspension / Wheel Travel

Double wishbone/11.0 in

Rear Suspension / **Wheel Travel**

Double wishbone/10.1 in

Front Tires 26 x 9.00-12, radial **Rear Tires** 26 x 11.00-12, radial

Electric Power Steering (EPS), Tilt steering Steering

Dual Disc, 1 piston caliper

Park Brake Type Independent, Mechanical Disc

Front Brakes Dual Disc, 2 piston caliper **Rear Brakes**

Instruments

Multi-function display includes digital speedometer, fuel gauge, odometer, hour meter, clock, dual trip meters, 2WD/4WD indicator, water temperature warning

indicator, oil pressure warning indicator, fuel injection warning indicator, CVT and EPS warning indicators, neutral, reverse and parking indicators, seatbelt

reminder lamps

Additional Features Roof, Additional Front Cup Holders

Color Choices

TRUETIMBER® STRATA

Warranty

Kawasaki STRONG 3-Year Limited Warranty

Scan with camera to view videos, key features and more.

