
MULE PRO-MX™ EPS









POWER

Engine 4-stroke, single cylinder, SOHC, 4-valve liquid-cooled

Displacement

42.7 lb-ft @ 5,000 rpm **Maximum Torque**

Bore x Stroke 102.0 x 85.0mm

Compression Ratio 10.3:1

Fuel System DFI® with 44mm throttle body

Continuously Variable Transmission (CVT) with centrifugal Transmission

Final Drive Selectable 2WD/4WD, shaft Dual mode rear differential with

differential lock

Engine Braking Yes

Alternator Output 35.7 amp

(max)

Ground Clearance 10.6 in **Fuel Capacity** 9.5 gal

Turning Radius 14.0 ft

Cargo Bed **Dimensions (LxWxH)**

33.4 x 44.1 x 9.1 in

Cargo Bed Load

Capacity

699 lb / 600 lb CA Model

Payload Capacity 1,200 lb

Seating Capacity

Towing Capacity 1,500 lb

Lighting (2) Halogen headlights. (2) LED headlights

CAPABILITY

Front Suspension / Double wishbone/8.6 in Wheel Travel

Rear Suspension / Double wishbone/9.1 in

Wheel Travel

Front Tires 25 x 8.00-12, radial **Rear Tires** 25 x 10.00-12, radial

Electric Power Steering (EPS), Tilt steering Steering

Park Brake Type Independent, Mechanical Disc

Dual Disc, 2 piston caliper **Rear Brakes**

Dual Disc, 1 piston caliper

DETAILS

Overall Length 110.0 in **Overall Width** 60.0 in **Overall Height** 74.4 in

Curb Weight 1,587.6 lb* / 1,589.8 lb* CA Model

Wheelbase 78.9 in

Multi-function display includes digital speedometer, fuel Instruments gauge, odometer, hour meter, clock, dual trip meters,

2WD/4WD indicator, water temperature warning indicator, EPS warning indicators, neutral, reverse and parking indicators, differential indicator lamp, seatbelt reminder

lamps

Wheel Type Steel

Color Choices Timberline Green, Firecracker Red

Warranty Kawasaki STRONG 3-Year Limited Warranty

Kawasaki Protection 12, 24, 36, or 48 months Plus™ (optional)

Scan with camera to view videos, key features and more.

Front Brakes

