







POWER

Engine 4-stroke, SOHC, 4-valve V-twin, liquid-cooled

Displacement 783cc

Maximum Torque 47.0 lb-ft @ 5,500 rpm

Bore x Stroke 85.0 x 69.0mm

Compression Ratio 10.7:1

Fuel System DFI® with two 36mm Mikuni throttle bodies

TCBI with Electronic Advance Ignition

Starting System Electric

Transmission Automatic CVT with centrifugal clutch (H,L,N,R)

Final Drive Selectable 2WD/4WD with locking front differential, shaft

Engine Braking Yes **Turning Radius** 16.7 ft

Cargo Bed 27.6 x 43.3 x 10.4 in **Dimensions (LxWxH)**

7.9 gal

600 lb

Cargo Bed Load

Capacity

Fuel Capacity

Payload Capacity 1,109 lb

Seating Capacity

Towing Capacity 1,300 lb

(2) halogen headlights, (2) incandescent taillights, Lighting

incandescent stoplight

CAPABILITY

Front Suspension / Wheel Travel

Double Wishbone; FOX Podium coil-over shocks with piggyback reservoir, adjustable preload and 24-way

compression damping/8.0 in

Rear Suspension / Wheel Travel

Rear Tires

Double Wishbone; FOX Podium coil-over shocks with piggyback reservoir, adjustable preload and 24-way

compression damping/8.3 in

Front Tires Maxxis® 26 x 9-12

Electric Power Steering (EPS) / rack-and-pinion **Steering**

Maxxis® 26 x 11-12

Front Brakes Dual hydraulic discs with two-piston calipers

Sealed, oil-bathed, multi-disc **Rear Brakes**

Ground Clearance 11.2 in

DETAILS

Steel Tube Double-X Reinforcement Frame

Overall Length 118.1 in **Overall Width** 60.0 in **Overall Height** 75.8 in

Curb Weight 1,570.0 lb* / 1,572.2 lb* CA Model

Wheelbase 85.8 in

Instruments Multi-function digital meter with speedometer, fuel gauge, clock, hour meter, odometer, dual trip meter and

parking-brake indicator, R/N/P/4WD, water temp and

low-oil-pressure indicators

Wheel Type Steel

Color Choices Metallic Moondust White/Super Black

Warranty Kawasaki Strong 3-Year Limited Warranty

Kawasaki Protection 12, 24, or 36 months Plus™ (optional)

Scan with camera to view videos. key features and more.

