TERYX KRX® 1000 eS







| D | N | ١ | N | E | D |
|---|---|---|---|---|---|
| | | м | N | г | π |

4-stroke, DOHC, 8-valve parallel-twin, liquid cooled **Engine**

Displacement 999cc

Maximum Torque 76.7 lb-ft @ 7,000 rpm

Bore x Stroke 92.0 x 75.1mm

Compression Ratio

Fuel System DFI® with two 50mm throttle bodies

TCBI with Flectronic Advance Ignition

Starting System Electric

Automatic CVT with centrifugal clutch (H,L,N,R) **Transmission**

Final Drive

Engine Braking

Selectable 2WD/4WD with locking front differential, shaft

CAPABILITY

Front Suspension / Double wishbone, FOX 2.5 Podium Live Valve Internal Bypass Wheel Travel shocks with piggyback reservoir, fully adjustable preload,

and KECS controlled compression damping/18.6 in

Rear Suspension / 4-link trailing-arm rear suspension, FOX 2.5 Podium Live **Wheel Travel** Valve Internal Bypass shocks with piggyback reservoir, fully adjustable preload, and KECS controlled compression

damping/21.1 in

Front Tires Maxxis® Carnivore 31 x 10.00R15 8PR

Rear Tires Maxxis® Carnivore 31 x 10.00R15 8PR

Steering Electric Power Steering (EPS) / rack-and-pinion

Front Brakes Dual hydraulic discs with two-piston calipers

Rear Brakes Dual hydraulic discs with single-piston calipers

14.4 in (max), 14.0 in (std) **Ground Clearance**

Fuel Capacity 10.6 gal **Turning Radius** 20.3 ft

Cargo Bed 14.6 x 33.1 x 9.1 in Dimensions (LxWxH)

351 lb **Cargo Bed Load**

Capacity

Payload Capacity 781 lb

Seating Capacity

Towing Capacity N/A

Lighting (2) LED headlights, (2) LED taillights, LED stoplight

DETAILS

Frame Ladder type, tubular steel

Overall Length 132.1 in **Overall Width** 68.1 in **Overall Height** 77.0 in

Curb Weight 1,944.8 lb* / 1,947.0 lb* CA Model

Wheelbase

Instruments Multi-function digital meter with bar-style tachometer (2

display options), digital speedometer, bar-style fuel gauge, gear indicator (L, H, N, R), Power Mode, driving mode (2WD/4WD/4WD+Diff Lock) indicator, Economical Riding Indicator, clock, odometer, dual trip meters, hour meter, water temperature, digital battery gauge, bar-style CTV temperature, seatbelt warning lamp, oil warning lamp, engine check lamp, water temperature warning lamp, neutral indicator lamp, reverse indicator lamp, parking indicator lamp, EPS warning lamp, and CVT belt warning lamp.

Additional Features Roof, Front Bumper

Color Choices Ice Gray/Metallic Onyx Black 6 Month Limited Warranty Warranty

Scan with camera to view videos,

key features

and more.



*Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied). KAWASAKI CARES: Read Owner's Manual and all on-product warnings. Warning: The Teryx® side x side can be hazardous to operate. For your safety: Always wear a helmet, eye protection and protective clothing. Never operate under the influence of drugs or alcohol. Avoid excessive speeds and stunt driving. Be extra careful on difficult terrain. Protect the environment. The Kawasaki Teryx side x side is an off-highway vehicle only, and is not designed, equipped or manufactured for use on public streets, roads or highways. ©2025 Kawasaki Motors Corp., U.S.A. Specifications subject to change. Visit hawaii.kawasaki.com for full product details.