TERYX KRX®4 1000 eS









POWER

Engine 4-stroke, DOHC, 8-valve parallel-twin, liquid cooled

Displacement 999c

Maximum Torque 76.7 lb-ft @ 7,000 rpm

Bore x Stroke 92.0 x 75.1mm

Compression Ratio 11.5:

Fuel System DFI® with two 50mm throttle bodies

Ignition TCBI with Electronic Advance

Starting System Electric

Transmission Automatic CVT with centrifugal clutch (H,L,N,R)

Final Drive Selectable 2WD/4WD with locking front differential, shaft

Engine Braking Yes

Fuel Capacity 10.6 gal

Cargo Bed 14.6 x 33.1 x 9.1 in Dimensions (LxWxH)

Cargo Bed Load

Turning Radius

Capacity

Payload Capacity 1,001 lb

Seating Capacity

Towing Capacity N/A

Lighting (2) LED headlights, (2) LED taillights, LED stoplight

CAPABILITY

Front Suspension / Wheel Travel

Double wishbone, FOX 2.5 Podium Live Valve Internal Bypass shocks with piggyback reservoir, fully adjustable preload, and KECS controlled compression damping/18.6 in

Rear Suspension / Wheel Travel 4-link trailing-arm rear suspension, FOX 2.5 Podium Live Valve Internal Bypass shocks with piggyback reservoir, fully adjustable preload, and KECS controlled compression

damping/21.1 in

Front Tires Maxxis® Carnivore 31 x 10.00R15 8PR

Rear Tires Maxxis® Carnivore 31 x 10.00R15 8PR

Steering Electric Power Steering (EPS) / rack-and-pinion

Front Brakes Dual hydraulic discs with two-piston calipers

Rear Brakes Dual hydraulic discs with single-piston calipers

15.2 in (max), 14.2 in (std)

DETAILS

Frame Ladder type, tubular steel

23.3 ft

351 lb

4

Overall Length 157.3 in
Overall Width 68.1 in
Overall Height 76.2 in

Curb Weight 2,105.8 lb* / 2,108.0 lb* CA Model

Wheelbase 125.8 in

Instruments

Multi-function digital meter with bar-style tachometer (2 display options), digital speedometer, bar-style fuel gauge, gear indicator (L, H, N, R), Power Mode, driving mode (2WD/4WD/4WD+Diff Lock) indicator, Economical Riding Indicator, clock, odometer, dual trip meters, hour meter, water temperature, digital battery gauge, bar-style CTV temperature, seatbelt warning lamp, oil warning lamp, engine check lamp, water temperature warning lamp, neutral indicator lamp, reverse indicator lamp, parking

indicator lamp, EPS warning lamp, and CVT belt warning lamp.

Color Choices Candy Lime Green/Super Black

Warranty 6 Month Limited Warranty

Scan with camera to view videos, key features and more.

Ground Clearance



*Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied).

KAWASAKI CARES: Read Owner's Manual and all on-product warnings. Warning: The Teryx® side x side can be hazardous to operate. For your safety: Always wear a helmet, eye protection and protective clothing. Never operate under the influence of drugs or alcohol. Avoid excessive speeds and stunt driving. Be extra careful on difficult terrain. Protect the environment. The Kawasaki Teryx side x side is an off-highway vehicle only, and is not designed, equipped or manufactured for use on public streets, roads or highways. ©2025 Kawasaki Motors Corp., U.S.A.

Specifications subject to change. Visit hawaii.kawasaki.com for full product details.