

2024

VERSYS® -X 300 ABS

Kawasaki
Let the Good Times Roll®



PEARL MATTE SAGE GREEN/METALLIC MATTE CARBON GRAY



POWER

| | |
|------------------------------|---|
| Engine | 4-stroke, 2-cylinder, DOHC, liquid-cooled |
| Displacement | 296cc |
| Bore x Stroke | 62.0 x 49.0mm |
| Compression Ratio | 10.6:1 |
| Maximum Torque | 19.2 lb-ft |
| Fuel System | DFI® with 32mm throttle bodies (2) |
| Ignition | TCBI with Digital Advance |
| Transmission | 6-speed, return shift |
| Final Drive | Sealed chain |
| Electronic Rider Aids | Anti-lock Brake System (ABS), Economical Riding Indicator |

| | |
|---------------------|------------------------|
| Front Tire | 100/90-19M/C 57S |
| Rear Tire | 130/80-17M/C 65S |
| Front Brakes | Single 290mm disc, ABS |
| Rear Brakes | Single 220mm disc, ABS |

DETAILS

| | |
|-------------------------|---|
| Frame Type | Tubular, diamond |
| Rake/Trail | 24.3° / 4.3 in |
| Overall Length | 85.4 in |
| Overall Width | 33.9 in |
| Overall Height | 54.7 in |
| Ground Clearance | 7.1 in |
| Seat Height | 32.1 in |
| Curb Weight | 385.9 lb* |
| Fuel Capacity | 4.5 gal |
| Wheelbase | 57.1 in |
| Color Choices | Pearl Matte Sage Green/Metallic Matte Carbon Gray |
| Warranty | 12 Month Limited Warranty |

PERFORMANCE

| | |
|--|--|
| Front Suspension / Wheel Travel | Telescopic fork/5.1 in |
| Rear Suspension / Wheel Travel | Uni-Trak® swingarm with 5-way spring preload adjustment/5.8 in |

Scan with camera to view videos, key features and more.



*Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied). KAWASAKI CARES: Read Owner's Manual and all on-product warnings. Always wear a helmet, eye protection and proper apparel. Never ride under the influence of drugs or alcohol. Adhere to the maintenance schedule in your Owner's Manual. ©2025 Kawasaki Motors Corp., U.S.A. Specifications subject to change. Visit hawaii.kawasaki.com for full product details.