BRUTE FORCE® 750









POWER

Engine 4-stroke, V-twin, SOHC, liquid-cooled

Displacement 749cc

Bore x Stroke 85.0 x 66.0mm

Compression Ratio

Maximum Torque 42.7 lb-ft @ 4,750 rpm

Fuel System DFI® with two 34mm throttle bodies

Digital DC-CDI Ignition

Transmission Automatic Continuously Variable Transmission (CVT) with

Final Drive Selectable 2WD/4WD with variable control front differential

lock, shaft

DETAILS

Rear

Lighting

Turning Radius

Towing Capacity

Total Rack Capacity

Rack Capacity, Front/

Frame Type Double-cradle, high-tensile tubular steel

661.5 lb**

10.5 ft

1,250 lb

264.5 lb

88.0/176.0 lb

All-LED lighting

Tread Width 37.0/35.6 in **Overall Length** 86.0 in **Overall Width** 46.1 in **Overall Height** 47.6 in **Seat Height** 35.2 in

Curb Weight 707.8 lb*

Wheelbase 50.6 in

Instruments

Estimated Dry Weight

Digital speedometer, 2WD/4WD drive indicator, fuel gauge, odometer, dual trip meters, dual hour meter, clock (12h/24h),

battery voltage, Kawasaki service reminder, oil change reminder, high beam, neutral, reverse, and warning lights (engine, coolant temperature, CVT, oil, and battery voltage)

Special Features Full-color TFT Instrumentation w/ Smartphone Connectivity

via RIDEOLOGY THE APP POWERSPORTS, KQR™ system

Color Choices Timberline Green

Warranty 12 Month Limited Warranty

Kawasaki Protection 12, 24, 36 or 48 months Plus™ (optional)

CAPABILITY

Front Suspension / **Wheel Travel**

Double wishbone, adjustable spring preload/6.9 in

Rear Suspension / **Wheel Travel**

Double wishbone, adjustable spring preload/7.4 in

Front Tires

AT 25 x 8-12 AT 25 x 10-12

Front Brakes

Rear Brakes

Dual hydraulic 176mm discs with 2-piston calipers

Sealed, oil-bathed, multi-disc with independent park brake

Ground Clearance

9.0 in/9.7 in (max preload)

Starting System

Electric

Fuel Capacity

5.0 gal

Steering

Rack-and-pinion

Scan with camera to view videos, key features and more.



*Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied). **Dry weight does not include all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied). KAWASAKI CARES: Read Owner's Manual and all on-product warnings. Warning: ATVs can be hazardous to operate. For your safety: Always wear a helmet, eye protection, and protective clothing. Never carry a passenger. Never ride under the influence of drugs or alcohol. Never ride on public roads or pavement. Avoid excessive speeds and stunt driving. Be extra careful on difficult terrain. Kawasaki ATVs with engines over 90cc are recommended for use only by persons 16 years of age or older. Kawasaki also recommends that all ATV riders take a training course. For more information, see your dealer, call the ATV Safety Institute at 1-800-887-2887, or go to www.atvsafety.org. ©2025 Kawasaki Motors Corp., U.S.A. Specifications subject to change. Visit hawaii.kawasaki.com for full product details.