## KLX®230R









## **POWER**

Engine 4-stroke, single-cylinder, SOHC, air-cooled

Displacement 233cc

Bore x Stroke 67.0 x 66.0mm

Compression 9.4:1

Ratio

Fuel System DFI® with 32mm Keihin throttle body

Ignition TCBI with electronic advance

**Transmission** 6-speed, return shift with wet multi-disc

manual clutch

Final Drive Chain

**Rear Tire** 100/100-18

Front Brakes Single 240mm petal disc with a dual-

piston caliper

**Rear Brakes** Single 220mm petal disc with single-

piston caliper

## **PERFORMANCE**

Front
Suspension /
Wheel Travel

Rear
Suspension /
Wheel Travel

Uni-Trak® linkage system and single shock with adjustable spring preload/9.8 in

Wheel Travel

Front Tire

80/100-21

## **DETAILS**

Frame Type High-tensile steel, box-section perimeter

Rake/Trail 25.4°/4.2 in

Overall Length 80.5 in

Overall Width 33.3 in

Overall Height 47.2 in

Clearance

Ground

Seat Height 35.6 in

**Curb Weight** 262.4 lb\* / 264.5 lb\* 50-State Model

Fuel Capacity 1.7 gal

Wheelbase 54.1 in

**Color Choices** Lime Green, Battle Gray

11.4 in

**Warranty** 6 Month Limited Warranty



