

2025

KLX®300R


● LIME GREEN

● BATTLE GRAY


POWER

Engine	4-stroke, single-cylinder, DOHC, liquid-cooled
Displacement	292cc
Bore x Stroke	78.0 x 61.2mm
Compression Ratio	11.0:1
Fuel System	DFI® with 34mm Keihin throttle body
Ignition	TCBI with electronic advance
Transmission	6-speed, return shift with wet multi-disc manual clutch
Final Drive	Chain

PERFORMANCE

Front Suspension / Wheel Travel	43mm inverted telescopic fork with adjustable compression damping/11.2 in
Rear Suspension / Wheel Travel	Uni-Trak® gas charged shock with piggyback reservoir with adjustable compression, rebound damping and spring preload/11.2 in
Front Tire	3.0 x 21

Rear Tire	4.6 x 18
Front Brakes	Single 270mm petal disc with a dual-piston caliper
Rear Brakes	Single 240mm petal disc with single-piston caliper

DETAILS

Frame Type	Semi-double cradle
Rake/Trail	26.9° / 4.3 in
Overall Length	86.6 in
Overall Width	32.5 in
Overall Height	49.0 in
Ground Clearance	11.8 in
Seat Height	35.4 in
Curb Weight	282.2 lb* / 286.7 lb* 50-State Model
Fuel Capacity	2.1 gal
Wheelbase	56.5 in
Color Choices	Lime Green, Battle Gray
Warranty	6 Month Limited Warranty

Scan with camera
to view videos,
key features
and more.



*Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied). KAWASAKI CARES: Read Owner's Manual and all on-product warnings. Always wear a helmet, eye protection and proper apparel. Never ride under the influence of drugs or alcohol. Adhere to the maintenance schedule in your Owner's Manual. ©2026 Kawasaki Motors Corp., U.S.A. Specifications subject to change. Visit hawaii.kawasaki.com for full product details.

Kawasaki
Let the Good Times Roll®