







POWER

Engine 2-stroke, single-cylinder, liquid-cooled

Displacement 64cc

Bore x Stroke 44.5 x 41.6mm

Compression

Ratio

8.4:1

Fuel System 24mm Mikuni carburetor

Ignition CDI with Digital Advance

Transmission 6-speed, return shift, with wet multi-disc

manual clutch

Final Drive Chain

Rear Tire 80/100-12

Front Brakes Single 180mm disc with single-piston caliper

Rear Brakes Single 180mm disc with single-piston caliper

DETAILS

Frame Type High-tensile steel semi-double cradle

Rake/Trail 27.0°/2.4 in

Overall Length 62.6 in

Overall Width 29.9 in

Overall Height 37.6 in

Ground 12.0 in Clearance

Seat Height 29.9 in

Curb Weight 132.2 lb*

Fuel Capacity 1.0 gal

Wheelbase 44.1 in

Color Choices Lime Green

Warranty Not Available

PERFORMANCE

Front
Suspension /
Wheel Travel

33mm leading axle telescopic fork with 4way rebound damping/8.3 in

Rear Suspension / Wheel Travel Uni-Trak® single shock system with stepless 3-turns rebound damping and fully adjustable spring preload/9.4 in

Front Tire

60/100-14



