MULE™ 4010 4x4









POWER

Engine 4-stroke, 2-cylinder, OHV, 90° V-twin, Liquid-cooled

Displacement 617cc

Maximum Torque 34.7 lb-ft @ 2,500 rpm

Bore x Stroke 76.0 x 68.0mm

Compression Ratio

Fuel System DFI® with 34mm Mikuni throttle body

Transmission Continuously Variable Transmission (CVT) with (H,L,N,R)

Final Drive Selectable 2WD/4WD, shaft. Dual mode rear differential

with differential lock

Engine Braking

Alternator Output

(max)

23 amp

Rear Brakes	Drum
Ground Clearance	6.9 in
Fuel Capacity	6.3 gal
Turning Radius	11.2 ft
Cargo Bed Dimensions (LxWxH)	46.3 x 51.6 x 11.4 in
Cargo Bed Load Capacity	800 lb
Payload Capacity	1,327 lb
Seating Capacity	2
Towing Capacity	1,200 lb

(2) Halogen headlights, (2) tail/brake lights

CAPABILITY

Front Suspension / MacPherson Strut/3.9 in **Wheel Travel**

Rear Suspension / Wheel Travel

DeDion Axle/2.8 in

Front Tires

23 x 11-10

Rear Tires 23 x 11-10

Steering Rack-and-pinion w/ Electric Power Steering (EPS)

Park Brake Type

Front Brakes

Independent, mechanical drum

Drum

DETAILS

Lighting

Overall Length 116.7 in **Overall Width** 62.0 in **Overall Height** 75.8 in **Curb Weight** 1,433.3 lb* Wheelbase 73.6 in Instruments Parking brake warning light, coolant temperature warning light, 12V DC outlet, fuel gauge, hour meter **Color Choices** Timberline Green, Dark Royal Red Warranty Kawasaki STRONG 3-Year Limited Warranty



