## **MULE PRO-DX™ EPS**









## **POWER**

**Engine** 4-stroke, 3-cylinder, OHV, liquid-cooled, diesel

Displacement 993cc

**Maximum Torque** 38.3 lb-ft @ 2,400 rpm

74.0 x 77.0mm **Bore x Stroke** 

**Compression Ratio** 23.5:1

Bosch in-line injection pump **Fuel System** 

Continuously Variable Transmission (CVT) with (H,L,N,R) **Transmission** 

**Final Drive** Selectable 2WD/4WD, shaft. Dual mode rear differential

with differential lock

**Engine Braking** Yes

**Alternator Output** 

(max)

55 amp

## CAPABILITY

Front Suspension / **Wheel Travel** 

Double wishbone/8.7 in

Rear Suspension / Wheel Travel

Double wishbone/8.5 in (L)/8.7 in (R)

**Front Tires** 26 x 9-12

**Rear Tires** 26 x 11-12

Steering Electric Power Steering (EPS), Tilt steering

**Park Brake Type** Independent, mechanical disc

**Front Brakes** Dual disc, 2-piston caliper

Rear Brakes Dual disc, 1-piston caliper

**Fuel Capacity** 7.9 gal

**Turning Radius** 16.0 ft

**Cargo Bed** 

**Ground Clearance** 

**Dimensions (LxWxH)** 

**Cargo Bed Load** 

Capacity

**Payload Capacity** 1,574 lb

999 lb

10.4 in

54.1 x 53.7 x 11.0 in

**Seating Capacity** 3-person

**Towing Capacity** 2.000 lb

Lighting (2) Halogen headlights

## **DETAILS**

**Overall Length** 133.3 in

**Overall Width** 64.0 in

**Overall Height** 77.4 in

**Estimated Dry** 

Weight

1,781.6 lb\*\*

**Curb Weight** 

1,858.8 lb\*

Wheelbase

92.3 in

Instruments

Multi-function display includes digital speedometer, fuel gauge, odometer, hour meter, clock, dual trip meters,

2WD/4WD indicator, water temperature warning indicator, oil pressure warning indicator, glow plug indicator, CVT and EPS warning indicators, neutral, reverse and parking

indicators, seatbelt reminder lamps

**Color Choices** 

**Bright White** 

Warranty

Kawasaki STRONG 3-Year Limited Warranty

Scan with camera to view videos, key features and more.



'Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied). \*\*Dry weight does not include all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied). All MULE™ PRO Series side x side's Rollover Protective Structure (ROPS) meets the performance requirements of ISO 3471. KAWASAKI CARES: Read Owner's Manual and all on-product warnings. Always wear protective gear appropriate for the use of this vehicle. Never operate under the

influence of drugs or alcohol. Protect the environment. The Kawasaki MULE™ side x side is an off-highway vehicle only, and is not designed, equipped or manufactured for use on public streets, roads or highways. Obey the laws and regulations that control the use of your vehicle. ©2025 Kawasaki Motors Corp., U.S.A. Specifications subject to change. Visit hawaii.kawasaki.com for full product details.