## **MULE PRO-MX™ EPS**









## **POWER**

**Engine** 4-stroke, single cylinder, SOHC, 4-valve, liquid-cooled

Displacement 695cc

**Maximum Torque** 42.7 lb-ft @ 5,000 rpm

**Bore x Stroke** 102.0 x 85.0mm

**Compression Ratio** 10.3:1

**Fuel System** DFI® with 44mm throttle body

**Transmission** Continuously Variable Transmission (CVT) with

centrifugal clutch, (H,L,N,R)

**Final Drive** Selectable 2WD/4WD, shaft. Dual mode rear differential

with differential lock

**Engine Braking** 

**Alternator Output** 35.7 amp

(max)

**Rear Brakes** Dual disc, 1-piston caliper

**Ground Clearance** 10.6 in

**Fuel Capacity** 9.5 gal

**Turning Radius** 14.0 ft

Cargo Bed

**Dimensions (LxWxH)** 

699 lb / 600 lb CA Model

33.4 x 44.1 x 9.1 in

**Cargo Bed Load** Capacity

1,200 lb

**Payload Capacity** 

**Seating Capacity** 

**Towing Capacity** 1.500 lb

Lighting (2) Halogen headlights, (2) LED headlights

## CAPABILITY

Front Suspension / Double wishbone/8.6 in **Wheel Travel** 

Rear Suspension / **Wheel Travel** 

Double wishbone/9.1 in

**Front Tires** 

25 x 8-12, radial

**Rear Tires** 25 x 10-12, radial

Electric Power Steering (EPS), Tilt steering **Steering** 

**Park Brake Type** Independent, mechanical disc

**Front Brakes** Dual disc, 2-piston caliper

## **DETAILS**

**Overall Length** 110.0 in

**Overall Width** 60.0 in

**Overall Height** 74.4 in

**Curb Weight** 1,587.6 lb\* / 1,589.8 lb\* CA Model

Wheelbase 78.9 in

Instruments Multi-function display includes digital speedometer,

fuel gauge, odometer, hour meter, clock, dual trip meters, 2WD/4WD indicator, water temperature warning indicator, EPS warning indicators, neutral, reverse and parking indicators, differential indicator lamp, seatbelt

reminder lamps

**Color Choices** Timberline Green, Bright White

Warranty Kawasaki STRONG 3-Year Limited Warranty

Scan with camera to view videos, key features and more.



\*Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied). All MULE™ PRO Series side x side's Rollover Protective Structure (ROPS) meets the performance requirements of ISO 3471.