## **MULE PRO-MX™ SE**







P	N	V	V	F	R
•	·		•	L	

Engine 4-stroke, single cylinder, SOHC, 4-valve, liquid-cooled

Displacement 695cc

Maximum Torque 42.7 lb-ft @ 5,000 rpm

Bore x Stroke 102.0 x 85.0mm

Compression Ratio 10.3:1

Fuel System DFI® with 44mm throttle body

Transmission Continuously Variable Transmission (CVT) with centrifugal

clutch, (H,L,N,R)

Final Drive Selectable 2WD/4WD, shaft. Dual mode rear differential

with differential lock

Engine Braking Yes

**Alternator Output** 

(max)

35.7 amp

## **CAPABILITY**

Front Suspension / Do Wheel Travel

Double wishbone/8.6 in

Rear Suspension / Wheel Travel Double wishbone/9.1 in

Front Tires 25 x 8-12, radial

**Rear Tires** 25 x 10-12, radial

Steering Electric Power Steering (EPS), Tilt steering

Park Brake Type

Independent, mechanical disc

Front Brakes

Dual disc, 2-piston caliper

Rear Brakes

Dual disc, 1-piston caliper

Ground Clearance 10.6 in

Fuel Capacity 9.5 gal

Turning Radius 14.0 ft

Cargo Bed

Dimensions (LxWxH)

Cargo Bed Load Capacity

**Payload Capacity** 

У

Seating Capacity 2

cuting cupacity 2

Towing Capacity 1,500 lb

**Lighting** (2) Halogen headlights, (2) LED headlights

33.4 x 44.1 x 9.1 in

1,200 lb

699 lb / 600 lb CA Model

## **DETAILS**

Overall Length 110.0 in

Overall Width 60.0 in

Overall Height 75.8 in

**Curb Weight** 1,622.9 lb\* / 1,625.1 lb\* CA Model

Wheelbase 78.9 in

Instruments Multi-function display includes digital speedometer, fuel

gauge, odometer, hour meter, clock, dual trip meters, 2WD/4WD indicator, water temperature warning indicator, EPS warning indicators, neutral, reverse and parking indicators, differential indicator lamp, seatbelt

reminder lamps

Additional Features Roof, WARN® VRX 35 Winch, Cast Aluminum Wheels,

**Painted Body Panels** 

Color Choices Gold

Warranty Kawasaki STRONG 3-Year Limited Warranty

Scan with camera to view videos, key features and more.



\*Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied). All MULE™ PRO Series side x side's Rollover Protective Structure (ROPS) meets the performance requirements of ISO 3471.