2025

MULE SX™









POWER

Engine 4-stroke, single-cylinder, OHV, air-cooled

Displacement 401cc

Maximum Torque 20.6 lb-ft @ 2,200 rpm

82.0 x 76.0mm **Bore x Stroke**

Compression Ratio 8.3:1

Fuel System Nikki 6C1026 carburetor

Transmission Continuously Variable Transmission (CVT) with (H,L,N,R)

Final Drive 2WD, shaft. Dual mode rear differential with differential

lock

Engine Braking No

Alternator Output 17 amp

(max)

Front Brakes Drum **Rear Brakes** Drum **Ground Clearance** 6.1 in **Fuel Capacity** 4.2 gal **Turning Radius** 10.8 ft

Cargo Bed **Dimensions (LxWxH)**

Cargo Bed Load

Capacity

Payload Capacity 926 lb

Seating Capacity 2

Towing Capacity 1,100 lb**

Lighting (2) Halogen headlights, tail/brake lights

35.6 x 40.9 x 9.6 in

399 lb

CAPABILITY

Front Suspension / **Wheel Travel**

MacPherson Strut/3.1 in

Rear Suspension / Wheel Travel

Unit Swingarm/3.1 in

Front Tires 22 x 9-10 **Rear Tires**

22 x 11-10

Steering Rack-and-pinion

Park Brake Type

Independent, mechanical drum

DETAILS

Overall Length 106.7 in

Overall Width 52.6 in

Overall Height 70.1 in

Curb Weight 967.6 lb*

Wheelbase 70.1 in

Instruments Fuel gauge, hour meter, oil temp light, parking brake

light

Color Choices Grayish Blue, Super Black

Kawasaki STRONG 3-Year Limited Warranty Warranty

Scan with camera to view videos, key features and more.

