

2025

# NINJA® ZX™-14R ABS

**Kawasaki**  
Let the Good Times Roll®



METALLIC MATTE SOVEREIGN RED/  
METALLIC FLAT SPARK BLACK/METALLIC MATTE GRAPHITE  
GRAY



## POWER

<b>Engine</b>	4-stroke, in-line 4-cylinder, DOHC, 16-valve, liquid-cooled
<b>Displacement</b>	1,441cc
<b>Bore x Stroke</b>	84.0 x 65.0mm
<b>Compression Ratio</b>	12.3:1
<b>Maximum Horsepower</b>	197.0 hp <sup>1</sup> @ 10,000 rpm
<b>Maximum Torque</b>	116.5 lb-ft @ 7,500 rpm
<b>Fuel System</b>	DFI® with 44mm Mikuni throttle bodies (4)
<b>Ignition</b>	TCBI with Electronic Advance
<b>Transmission</b>	6-speed, return shift
<b>Final Drive</b>	Sealed chain
<b>Electronic Rider Aids</b>	Economical Riding Indicator, Kawasaki TRaction Control (KTRC) (3-mode), Power Modes, Anti-lock Brake System (ABS)

## PERFORMANCE

<b>Front Suspension / Wheel Travel</b>	43mm inverted cartridge fork with adjustable preload, 18-way compression and 15-way rebound damping adjustment/4.6 in
----------------------------------------	-----------------------------------------------------------------------------------------------------------------------

## Rear Suspension / Wheel Travel

Bottom-link Uni-Trak® and gas-charged shock with adjustable preload, stepless rebound and compression damping adjustments, adjustable ride height/4.9 in

## Front Tire

120/70-17

## Rear Tire

190/50-R17

## Front Brakes

Dual 310mm semi-floating Brembo discs with dual radial-mounted Brembo 4-piston M50 monobloc calipers and ABS

## Rear Brakes

Single 250mm disc with twin-piston caliper and ABS

## DETAILS

<b>Frame Type</b>	Aluminum monocoque
<b>Rake/Trail</b>	23.0° /3.7 in
<b>Overall Length</b>	85.4 in
<b>Overall Width</b>	30.3 in
<b>Overall Height</b>	46.1 in
<b>Ground Clearance</b>	4.9 in
<b>Seat Height</b>	31.5 in
<b>Curb Weight</b>	593.1 lb*
<b>Fuel Capacity</b>	5.8 gal
<b>Wheelbase</b>	58.3 in
<b>Color Choices</b>	Metallic Matte Sovereign Red/Metallic Flat Spark Black/Metallic Matte Graphite Gray
<b>Warranty</b>	12 Month Limited Warranty

Scan with camera  
to view videos,  
key features  
and more.



\*Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied).

<sup>1</sup>This vehicle's HP was measured according to ISO standard 4106. This ISO standard measures HP differently than the SAE standards by which the horsepower of

many cars is measured, and as a result the referenced HP measurement may be higher than if it were measured by an SAE standard.

KAWASAKI CARES: Read Owner's Manual and all on-product warnings. Always wear a helmet, eye protection and proper apparel. Never ride under the influence of

drugs or alcohol. Adhere to the maintenance schedule in your Owner's Manual. ©2026 Kawasaki Motors Corp., U.S.A.

Specifications subject to change. Visit [hawaii.kawasaki.com](http://hawaii.kawasaki.com) for full product details.