
## NINJA® ZX™-14R ABS









## **POWER**

**Engine** 4-stroke, in-line 4-cylinder, DOHC, 16-valve, liquid-

cooled

1,441cc Displacement

**Bore x Stroke** 84.0 x 65.0mm

**Compression Ratio** 12.3:1

Maximum Horsepower 197.0 hp<sup>1</sup> @ 10,000 rpm

**Maximum Torque** 116.5 lb-ft @ 7,500 rpm

DFI® with 44mm Mikuni throttle bodies (4) **Fuel System** 

Ignition TCBI with Electronic Advance

**Transmission** 6-speed, return shift

**Final Drive** Sealed chain

**Electronic Rider** 

Aids

Economical Riding Indicator, Kawasaki TRaction Control (KTRC) (3-mode), Power Modes, Anti-lock

Brake System (ABS)

## **PERFORMANCE**

Front Suspension / **Wheel Travel** 

43mm inverted cartridge fork with adjustable preload, 18-way compression and 15-way rebound damping adjustment/4.6 in

**Rear Suspension / Wheel Travel** 

Bottom-link Uni-Trak® and gas-charged shock with adjustable preload, stepless rebound and compression damping adjustments, adjustable ride

height/4.9 in

**Front Tire** 120/70-17

**Rear Tire** 190/50-R17

**Front Brakes** Dual 310mm semi-floating Brembo discs with dual

radial-mounted Brembo 4-piston M50 monobloc

**Rear Brakes** Single 250mm disc with twin-piston caliper and ABS

## **DETAILS**

**Frame Type** Aluminum monocoque

Rake/Trail 23.0°/3.7 in

**Overall Length** 85.4 in

**Overall Width** 30.3 in

**Overall Height** 46.1 in

**Ground Clearance** 4.9 in

**Seat Height** 31.5 in

**Curb Weight** 593.1 lb\*

**Fuel Capacity** 5.8 gal

Wheelbase 58.3 in

**Color Choices** Metallic Matte Sovereign Red/Metallic Flat Spark

Black/Metallic Matte Graphite Gray

12 Month Limited Warranty Warranty

Scan with camera to view videos, key features and more.

