



2025

RIDGE® XR CREW HVAC




-  ICE GRAY
-  METALLIC GRAYSTONE



POWER		DETAILS	
Engine	4-stroke, DOHC, 4-valve, in-line 4-cylinder, liquid-cooled	Fuel Capacity	12.9 gal
Displacement	999cc	Turning Radius	19.0 ft
Maximum Horsepower	116.0 hp <sup>1</sup> @ 8,500 rpm	Cargo Bed Dimensions (LxWxH)	34.6 x 49.0 x 12.8 in
Maximum Torque	73.8 lb-ft @ 8,000 rpm	Cargo Bed Load Capacity	1,000/600 lb CA Model
Bore x Stroke	73.4 x 59.0mm	Payload Capacity	1,290/1,076 lb CA Model
Compression Ratio	10.6:1	Seating Capacity	4-person (2 row), bucket seats
Fuel System	EFI	Towing Capacity	2,500 lb
Ignition	TCBI with Digital Advance	Lighting	All-LED lighting
Starting System	Electric		
Transmission	Continuously Variable Transmission (CVT) with (H,L,N,R)		
Final Drive	Selectable 4WD with locking front/rear differential, shaft		
Engine Braking	Yes		
Alternator Output (max)	85 amp		
Electronic Rider Aids	Power Modes, Economical Riding Indicator		
CAPABILITY			
Front Suspension / Wheel Travel	Long-Travel, Double Wishbone/12.7 in	Frame	Ladder type, tubular steel
Rear Suspension / Wheel Travel	Long-Travel, Double Wishbone/12.7 in	Overall Length	156.7 in
Front Tires	Duro 30 x 10-14	Overall Width	64.0 in
Rear Tires	Duro 30 x 10-14	Overall Height	82.7 in
Wheel Type	14" Aluminum	Estimated Dry Weight	2,403.5/2,405.7 lb** CA Model
Steering	Rack-and-pinion w/ Electric Power Steering (EPS)	Curb Weight	2,513.7/2,515.9 lb* CA Model
Front Brakes	Dual hydraulic 249mm discs with two-piston calipers	Wheelbase	122.2 in
Rear Brakes	Dual hydraulic 249mm discs with single-piston calipers	Instruments	Digital speedometer, tachometer, fuel gauge, odometer, dual trip meters, total time, trip time, average speed, gear indicator, Driving Mode, Power Mode, clock, water temperature, battery voltage, oil change reminder, Economical Riding Indicator, maintenance reminder, high beam, neutral, reverse, and warning lights (battery, EPS, CVT, seatbelt, parking indicator, oil pressure, water temperature)
Ground Clearance	14.4/15.2 in (max preload); 14.4 in CA Model	Additional Features	Full Cab with HVAC, Adjustable driver/passenger seats, ERGO-FIT®, Full-color TFT Instrumentation with Smartphone Connectivity via RIDEOLGY THE APP Powersports, USB ports, KQR™ system compatible
		Color Choices	Ice Gray, Metallic Graystone
		Warranty	Kawasaki STRONG 3-Year Limited Warranty

Scan with camera to view videos, key features and more.



\*Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied).

\*\*Dry weight does not include all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied).

<sup>1</sup>This vehicle's HP was measured according to ISO standard 4106. This ISO standard measures HP differently than the SAE standards by which the horsepower of many cars is measured, and as a result the referenced HP measurement may be higher than if it were measured by an SAE standard.

Specifications subject to change. Visit [hawaii.kawasaki.com](http://hawaii.kawasaki.com) for full product details.