RIDGE® XR HVAC









12.9 gal

15.0 ft

34.6 x 49.0 x 12.8 in

1,000/600 lb CA Model

1,275/875 lb CA Model

2, bucket seats

All-LED lighting

2.500 lb

POWER

4-stroke, DOHC, 4-valve, in-line 4-cylinder, liquid-cooled Engine

Displacement

Maximum Horsepower 116.0 hp1 @ 8,500 rpm **Maximum Torque** 73.8 lb-ft @ 8.000 rpm

Bore x Stroke 73.4 x 59.0mm

Compression Ratio 10.6:1 FFI

Fuel System

Ignition TCBI with Digital Advance

85 amp

Starting System Electric

Transmission Continuously Variable Transmission (CVT) with (H,L,N,R) **Final Drive** Selectable 4WD with locking front/rear differential, shaft

Engine Braking Yes

Alternator Output (max)

Electronic Rider Aids Power Modes, Economical Riding Indicator

DETAILS

Lighting

Fuel Capacity

Turning Radius

Cargo Bed Load

Payload Capacity

Seating Capacity

Towing Capacity

(LxWxH)

Capacity

Cargo Bed Dimensions

Ladder type, tubular steel Frame

Overall Length 125.4 in **Overall Width** 64.0 in **Overall Height** 82.3 in

Estimated Dry Weight 1,962.5/1,964.7 lb** CA Model **Curb Weight** 2.068.3/2.070.5 lb* CA Model

Wheelbase 90.7 in

Instruments

Digital speedometer, tachometer, fuel gauge, odometer, dual trip meters, total time, trip time, average speed, gear indicator, Driving Mode, Power Mode, clock, water temperature, battery voltage, oil change reminder, Economical Riding Indicator, maintenance

reminder, high beam, neutral, reverse, and warning lights (battery, EPS, CVT, seatbelt, parking indicator, oil pressure, water

Additional Features Full Cab with HVAC, Adjustable driver/passenger seats, ERGO-FIT®,

Full-color TFT Instrumentation with Smartphone Connectivity via RIDEOLOGY THE APP Powersports, USB ports, KQR™ system

compatible

Color Choices Ice Gray, Metallic Graystone

Warranty Kawasaki STRONG 3-Year Limited Warranty

CAPABILITY

Front Suspension / Wheel Travel

Rear Suspension / Wheel Travel

Front Tires

Rear Tires

Wheel Type

Steering **Front Brakes**

Rear Brakes

Ground Clearance

Dual hydraulic 249mm discs with two-piston calipers

Duro 30 x 10-14

Duro 30 x 10-14

14" Aluminum

Dual hydraulic 249mm discs with single-piston calipers 13.8/14.6 in (max preload); 13.9 in CA Model

Rack-and-pinion w/ Electric Power Steering (EPS)

Long-Travel, Double Wishbone/12.7 in

Long-Travel, Double Wishbone/12.7 in

Scan with camera to view videos, key features and more.

